Sulphur Dioxide Adsorption on Nickel Smelting Industry in East Luwu Using a Solution of Hydrogen Peroxide

Agus Dina¹, Muhammad Sjahrul¹, Muhammad Zakir¹, Dadang Ahmad Suriamihardja²

¹Department of Chemistry, Faculty of Mathematics and Natural Science, Hasanuddin University, Makassar, Indonesia

²Department of Physics, Faculty of Mathematics and Natural Science, Hasanuddin University, Makassar, Indonesia

Email address:

muhammadzakir@gmail.com (M. Zakir)

To cite this article:

Agus Dina, Muhammad Sjahrul, Muhammad Zakir, Dadang Ahmad Suriamihardja. Sulphur Dioxide Adsorption on Nickel Smelting Industry in East Luwu Using a Solution of Hydrogen Peroxide. *American Journal of Environmental Protection*. Vol. 5, No. 4, 2016, pp. 103-108.

doi: 10.11648/j.ajep.20160504.15

Received: June 22, 2016; **Accepted:** July 4, 2016; **Published:** July 16, 2016

Abstract: Research on SO₂ gas adsorption from emissions of nickel ore industries plant use coal in the smelting process and the production by using H₂O₂ as an adsorbent solution. The adsorbent used to reduce the level of SO₂ in the air pollution. This study includes the adsorption of SO₂ gas of 6 factory chimneys at the nickel ore industry (2 dryers, 2 kilns, and 2 furnaces). The results showed that the percentage ratio of the average absorbance between H₂O₂ and calcium carbonate in reducing greenhouse gas emissions of SO₂ into the air that is 95.00%: 93.34%. As for the rest of SO₂ gas unadsorbed fixed meet the quality standards specified (750 mg/m³). Batch adsorption was conducted with respect to concentration of adsorbent, the adsorption temperature, and contact time. It was shown that the optimum concentration of adsorbent was 5%, the adsorption temperature was 20°C, and contact time was 1800 second.

Keywords: SO₂ Gas, Hydrogen Peroxide, Gas Emission

1. Introduction

Total human population that continues to increase accompanied by increased their requirement and their activities. Diverse human activities have negative and positive impact on the environment. One of its negative effects that currently very disturbing is air pollution. According [16], air pollution is the presence of one or more physical substance, chemical, or biological in the atmosphere in an amount which can endanger the health of humans, animals and plants.

One of the substances that can cause air pollution is sulfur. Sulfur compounds in different forms has been known as a major air pollutant industrial areas as a result of burning fossil fuels, and can be derived from volcanic eruptions. In the future, an estimated amount of sulfur discharged into the atmosphere would have increased 10-fold [41]. In the form of gas, SO₂ can cause irritation to the lungs that causing hard to breathing especially for people who has asthma, children and the elderly. SO₂ is also able to react with other chemical compounds formed sulfate particles that if inhaled can

accumulate in the lungs and cause breathing problems, respiratory illnesses, and even death [9].

One of the industries that produce gas emission SO₂ is smelting industry Nickel located in Sorowako, East Luwu, South Sulawesi, where the production process is done by burning the raw material in the kiln-firing with coal and produce byproduct that is SO₂ [19]. The main problem that causing gas emissions SO₂ in the industry is coal as the main fuel, even if used is coal with the best quality (low sulfur content), sulfur dioxide will formed surely and estimated gas emissions SO₂ is wasted at least able to reach 13 tons/hour.

Reducing gas emissions SO₂ can be done with a wet scrubber systems, combustion flue gas is sprayed with slurry (lime slurry), Ca(OH)₂ were able to reduce SO₂ emissions of 88.5 thousand tons/year to 4.5 thousand tons/year or absorption SO₂ gas approximately 95% [24] but this process can produce CO₂ which is also one of the air pollutants. System wet scrubber also create problems with the chimney because there is spraying a slurry of lime on the chimney wall [43] and this system is costly because the industry had to prepare the land for mining and milling

limestone as well as land for waste disposal in a large capacity [48].

Based on the description above, it takes a process to reduce gas emissions SO_2 that are environmentally friendly and not damage the property industry. As it is known that the gas sulfur dioxide is a colorless, flammable and easily soluble in water, young oxidized, and can react with other compounds. Based on the chemical and physical properties, then the SO_2 can be removed by oxidation using oxidizing agent that is hydrogen peroxide and this reaction can produce sulfuric acid compound, so this research is carried out to reduce SO_2 gas emissions in the nickel industry located in the east Luwu using hydrogen peroxide.

2.1. Instrument

Figure 1. The series of instrument of SO_2 sampling.

Description of Instrument:

- A: Pipe sampling test;
- B: Flange;
- C: heater element;
- D: glass wool;
- E1, E2: adsorption bottle of 250 mL;
- F1, F2: junction three-cock;
- G: drying tube;
- H: wash bottle containing the adsorbent solution;
- I: aspirator pump;
- J: gas meter (capacity 1 L - 5 L per circle);
- K: gas meter thermometer;
- L: manometer;
- M: thermometer;
- N1: the cover faucet;
- N2: faucet flow rate regulator;
- O: rubber pipe (*flurorubber*);
- P: cooling container.

2.2. Material

The materials used in this research are hydrogen peroxide 30%, NaCl, HCl (37% w/v), Glycerol, Barium chloride (BaCl_2), Sulfuric acid (H_2SO_4) 0,1 N; Sodium tetraborate (boraks, $\text{Na}_2\text{B}_4\text{O}_7 \cdot 10\text{H}_2\text{O}$) 0,1 N; Indicator SM (sindur methyl) or MO (methyl orange) and Field blank solution.

2. Experimental

This research was carried out directly on the nickel smelting industry in East Luwu. This research is qualitative and quantitative research on the amount of SO_2 can react with the hydrogen peroxide. Samples emissions of SO_2 that get as laboratory scale using an instrument (Figure 1) and there are variation on concentrations, temperature and time of hydrogen peroxide to react with SO_2 . This process is carried out at the time when the industry is operating in conditions of temperature, flow rate and pressure of maximum emissions. SO_2 concentration was measured using a UV - Vis spectrophotometer.

3. Results and Discussion

Sampling and adsorption exhaust gas emissions industry conducted for twelve days in May 2015. The sampling is done where the condition of each chimney in a state of maximum 6 industrial chimney, each on 2 chimney dryer, 2 chimney Kiln, and 2 chimney furnace. The sampling

technique uses a series of side tool probe, vacuum for sucking in air emissions and a series of impinger a place for adsorbent solution (hydrogen peroxide). To view the results adsorption of SO₂ gas, then conducted sample analysis in

Laboratory Technical Implementation Unit of the Environment Agency of South Sulawesi province. Description of adsorption results concentration of SO₂ of each the chimney can be seen in the following chart.

Table 1. Results of adsorption concentration of SO₂ gas in chimneys emissions based on variations concentration of adsorbent solution.

No	Concentration (%)	Results (mg/M ³)					
		Hydrogen peroxide					
		Dryer 1	Dryer 2	Kiln 1	Kiln 2	Furnace 1	Furnace 2
1	1	2,585.25	3,185.07	4,093.89	3,031.75	6,345.13	6,495.09
2	2	4,558.59	4,383.21	4,717.91	3,432.83	6,462.34	6,290.94
3	3	5,545.59	4,390.07	4,949.44	3,790.89	8,414.79	8,052.81
4	4	4,824.26	5,468.10	6,067.79	4,548.50	8,570.97	8,406.47
5	5	5,562.36	5,610.57	7,805.51	6,099.64	10,501.50	10,590.40

Table 2. Results of adsorption concentration of SO₂ gas in chimneys emissions by temperature variations of adsorbent solution.

No	Temp. (°C)	Results (mg/M ³)					
		Hydrogen peroxide					
		Dryer 1	Dryer 2	Kiln 1	Kiln 2	Furnace 1	Furnace 2
1	20	5,328.14	5,377.72	6,674.04	5,316.34	9,613.78	10,015.3
2	25	4,526.98	4,988.47	6,466.24	4,381.93	9,603.76	8,610.69
3	30	4,083.60	4,918.19	6,006.50	3,854.37	8,433.09	8,563.33
4	35	3,437.75	4,765.20	4,018.89	3,694.13	7,257.47	6,373.46
5	40	2,780.29	3,333.34	3,573.66	2,852.99	6,229.25	6,236.93

Table 3. Results of adsorption concentration of SO₂ gas in chimneys emissions based on time variation of adsorbent solution.

No	Time (second)	Results (mg/M ³)					
		Hydrogen peroxide					
		Dryer 1	Dryer 2	Kiln 1	Kiln 2	Furnace 1	Furnace 2
1	600	2,880.02	2,650.28	3,698.88	2,796.12	5,789.36	4,584.16
2	900	3,389.42	3,665.24	4,864.09	3,222.10	6,741.13	5,528.04
3	1200	4,673.73	4,305.88	5,552.45	4,538.86	8,455.43	8,149.12
4	1500	4,937.86	5,097.07	6,559.05	5,267.34	9,685.90	8,101.28
5	1800	5,447.36	5,585.66	7,466.57	6,019.59	10,271.01	10,249.52

Figure 2. Results of adsorption concentration of SO₂ gas in chimneys emissions based on variations concentration of adsorbent solution.

Figure 3. Results of adsorption concentration of SO₂ gas in chimneys emissions by temperature variations of adsorbent solution.

Figure 4. Results of adsorption concentration of SO_2 gas in chimneys emissions based on time variation of adsorbent solution.

Based on the test data exhaust gas of SO_2 is absorbed by the hydrogen peroxide from chimneys emissions at dryer 1 and 2; kiln 1 and 2; and furnace 1 and 2, increased concentration of maximum adsorption indicated in the treatment adsorbent solution on the condition of 20°C , with a concentration of 5% and length taking 1800 seconds. Results achieved in the adsorption capability of the accumulation of means as follows:

1. Dryer 1, cylindrical chimney with a height of 61.6 meters with a diameter of 4 meters at coordinates $02^\circ34'8.3''$ LS and BT $121^\circ22'38.9''$ with a gas flow rate $327.82 \text{ m}^3/\text{sec}$. Conditions of the emission gas temperature 140°C , resulting adsorption 5479.29 mg/m^3 , $4623.62 \text{ tons/month}$ or 96.62% .
2. Dryer 2, cylindrical chimney with a height of 60.9 meters with 3.9 meter cross-sectional area at coordinates $02^\circ34'8.4''$ LS and BT $121^\circ22'39.5''$ with a gas flow rate $312.74 \text{ m}^3/\text{sec}$ in the emissions gas temperature conditions $\pm 140^\circ\text{C}$ produce adsorption 5361.79 mg/m^3 or $4348.41 \text{ tons/month}$ or 90.87% .
3. Kiln 1 (Reduced 1) is a cylindrical chimney with a height of 61 meters with 2.9 meter cross-sectional area at coordinates $02^\circ34'08.4''$ LS "and BT $121^\circ22'38.8''$ gas flow rate $234.87 \text{ m}^3/\text{sec}$ in the emission gas temperature conditions $\pm 168^\circ\text{C}$ produces adsorption $4454.99 \text{ tons/month}$ or 7315.25 mg/m^3 or 90.78% .
4. Kiln 2 (Reduction 2) is a cylindrical chimney with a height of 62 meters with 2.9 meter cross-sectional area at coordinates $02^\circ34'09.1''$ LS "and BT $121^\circ22'41.4''$ with a gas flow rate $291.39 \text{ m}^3/\text{sec}$ in the emissions gas temperature conditions $\pm 168^\circ\text{C}$ resulted adsorption $4387.95 \text{ tons/month}$ or 5811.85 mg/m^3 or 89.41% .
5. Furnace 1, cylindrical chimney with a height with a height of 61 meters with 4.1 meter cross-sectional area at coordinates $02^\circ34'09.4''$ LS "and BT $121^\circ22'42.9''$ with a gas flow rate $291.39 \text{ m}^3/\text{sec}$ in the emissions gas temperature conditions $\pm 200^\circ\text{C}$ produce adsorption $4720.00 \text{ tons/month}$ or 10128.76 mg/m^3 or 96.18% .
6. Furnace 2, cylindrical chimney with a height of 61 meters with 4.1 meter cross-sectional area at coordinates $02^\circ40'15.1''$ LS "and BT $121^\circ10'25.2''$. with a gas flow rate $291.39 \text{ m}^3/\text{sec}$ in the emissions gas temperature conditions $\pm 200^\circ\text{C}$ produce adsorption $4720.84 \text{ tons/month}$ or 10285.05 mg/m^3 or 96.19% .

Direct measurements of SO_2 gas emissions conducted in the same month of the dryer 1 with a gas flow rate $239.39 \text{ m}^3/\text{sec}$, dryer 2 with a gas flow rate $212.39 \text{ m}^3/\text{sec}$ produce an average of test results to produce $\pm 4785.43 \text{ tons/month}$ or equivalent to 8692.64 mg/m^3 , while from kiln 1 with a flow rate $171.52 \text{ m}^3/\text{sec}$ and kiln 2 with a flow rate $223.94 \text{ m}^3/\text{sec}$ produce an average of $\pm 4907.70 \text{ tons/month}$ or equivalent to 9622.94 mg/m^3 . Furnace 1 with a gas flow rate $236.63 \text{ m}^3/\text{sec}$ and furnace 2 with a gas flow rate $170 \text{ m}^3/\text{sec}$ also resulted in an average concentration $\pm 4907.7 \text{ tons/month}$ or equivalent to 9259.81 mg/m^3 .

Gas emissions that are not adsorbed from flue dryer 1 is $161.81 \text{ tons/month}$ or 190.59 mg/m^3 or 3.38% , dryer 2 is $437.02 \text{ tons/month}$ or 538.87 mg/m^3 or 9.13% , kiln 1 was $452.71 \text{ tons/month}$ or 743.37 mg/m^3 or 9.22% , kiln 2 was $519.75 \text{ tons/month}$ or 688.41 mg/m^3 or 10.59% , furnace 1 was $187.70 \text{ tons/month}$ or 402.79 mg/m^3 or 3.82% , and furnace 2 was $186.86 \text{ tons/month}$ or 407.10 mg/m^3 or 3.81% .

The results showed that the higher the temperature of the solution is getting lower to adsorb exhaust gas emissions, the lower the flow rate of the exhaust gas is getting greater the ability reaction of adsorbent and the nature of the gases emitted fluctuations in temperature, pressure and flow rate as well as the turbulence also affects the absorption of gas emissions factory chimneys.

Based on data from previous research using a slurry of lime (calcium hydroxide) which is able to adsorb sulfur dioxide by 95% equal to the adsorption ability of hydrogen peroxide that is 94.85% from industrial sources of nickel.

4. Conclusions

This result of this study that is comparison of percentage of the average adsorption accumulation between adsorbent solution using a solution of hydrogen peroxide and calcium carbonate slurry to reduce sulfur dioxide emissions into the ambient air show results approximately equal to the lime slurry that is 95.00% : 93.34% . The adsorption concentration of SO_2 greater if conditions adsorbent greater concentration, then the lower the temperature and the longer the adsorption time. Emissions of the six chimneys that are not adsorbed, they meet the standards set. under the rules of the Governor Number 69 Year 2010 on the quality standard emissions of SO_2 750 mg/m^3 , means that hydrogen peroxide as a adsorbent solution viable as an alternative instead of calcium carbonate.

References

- [1] Ahmed, I. B., P. K. Gbor, and C. Q. Jia, "Aqueous sulfur dioxide leaching of Cu, Ni, Co, Zn, and Fe from smelter slag in absence of oxygen," *Can. J. Chem. Eng.* 78(A) 694-703 (2000).
- [2] Ahmed, I. B., P. K. Gbor, and C. Q. Jia, "Effect of O_2 on aqueous SO_2 leaching of Co, Cu, and Ni from discard smelter slag," *Can. J. Chem. Eng.* 80(3) 410-420 (2002).

- [3] Arun Kumar Sharma, D. S. N. Prasad, Shveta Acharya, and Rashmi Sharma. Utility and Application of FGD System (Flue Gas Desulphurization) in Chemical and Environmental Engineering. *International Journal of Chemical Engineering and Applications*, Vol. 3, No. 2, April 2012.
- [4] Bhamidipati V. N. and W. C. Gibson (2003), Considerations for Low Sulfur Coal Blending, B. L. England Station, US.
- [5] Cahyadi, 2006. Strategi menurunkan emisi SO₂ pada PLTU batubara yang tidak memiliki fasilitas desulfurisasi. *Jurnal Ilmiah Teknologi Energi*, Vol.1, No.2. ISSN 1858–3466.
- [6] Cooper dan Alley, 1986. Air Pollution Control: A Design Approach. PWS Engineering, Boston.
- [7] Carn, S. A., Krueger, A. J., Krotkov, N. A., Yang, K., and Levelt, P. F., 2007, Sulfur dioxide emissions from Peruvian copper smelters detected by the Ozone Monitoring Instrument, *Geophys. Res. Lett.*, 34, L09801.
- [8] Davis and Cornwell, 1991. Introduction to Environmental Engineering. Second Edition.
- [9] Direktorat Batubara – ESDM, 2005. Data spesifikasi batubara perusahaan tambang batubara Indonesia tahun 2004, Jakarta, Indonesia.
- [10] ENV, Updated Report: Sulfur Dioxide Abatement Project Comparative Impact Assessment, 10 Februari 2011.
- [11] FastiaWininda dan Puji Lestari, 2006. Analisis karakteristik emisi cerobong dalam fasa gas pada industri semen yang menggunakan bahan bakar alternatif. Environmental Engineering Study Program. Faculty of Civil and Environment Engineering, ITB, Indonesia.
- [12] Ferron, C. J., 2008, Sulfur dioxide: a versatile reagent for the processing of cobaltic oxide minerals, *Journal of Metals*, 60(10), 50-54.
- [13] Habashi, F., 1976, Reduction of sulfates by hydrogen, *Can. J. Chem*, 54: 3646-3650.
- [14] Hatch., Carbon Footprint of SO₂ Scrubbing, PT. INCO, November 2010.
- [15] Hatfield, 2010, Distribution And Diversity Of Lichens And Bryophytes In Sorowako Area And Potential For Use As Indicators Of Air Quality.
- [16] Hutagalung, M. 2008. Teknologi Pengolahan Limbah Gas. Tersedia: <http://majarimagazine.com/2008/01/teknologi-pengolahan-limbahgas/>.
- [17] Ilari Ekman and Antti Ahti, 2004, Experiences of LIFAC FGD In Chinese Boiler, Proceeding China International Exhibition & Conference on SO_x and NO_x Reduction 2004, Beijing, P.R. China.
- [18] Kim Y. Z., J. K. Han, H. K. Hong, S. K. Lee, 1999, A Coal Blending Experience for the Reduction of Power Plant SO_x Emission, Samchonpo Thermal Power Site Division, KEPKO, KyongNam Province, Korea.
- [19] Laporan pelaksanaan RKL-RPL PT. INCO. 2006, 2008, 2009, 2010.
- [20] Martindale: The Complete Drug Reference 35th edition 2. AHFS 2008, elect. version 3. e-MIMS Australia, 2003 2006/2007 p.91 4. BNF 54th edition, elect. version. 5. DOEN 2008, hal.39, 68.
- [21] McDonald, R. G., and B. I. Whittington, 2008, Atmospheric acid leaching of nickel laterites review. Part I. Sulfuric acid technologies, *Hydrometallurgy*, 91 (1), 35-55.
- [22] Mudd, Gavin M., 2009, Nickel sulfide versus laterite: The hard sustainability challenge remains, proceedings of the 48th Annual Conference of Metallurgists, Canadian Metallurgical Society, Sudbury, Ontario, Canada.
- [23] Nur, M., Wirawan, B. Y., Wijaya, W. A., Suseno, A., Sumaryah, 2006, Pereduksian CO_x, NO_x, SO_x, HC, Dari Kendaraan Bermotor Dengan Menggunakan Plasma Nontermik, *Berkala Fisika*, 9 (4), 209-219 ISSN: 1410-9662.
- [24] Marosin, R., dan Anam, A., 2004, Karakteristik Emisi Gas Buang Insenerator Medis di Rumah Sakit Jiwa Dadi Makassar Sulawesi Selatan, *Jurnal Teknologi Lingkungan*, 5 (1).
- [25] Mulaudzi, N., and T. Mahlangu, 2009, Oxidative precipitation of Mn(II) from cobalt leach solutions using dilute SO₂/air mixture, paper presented at Hydrometallurgy Conference, The Southern African Institute of Mining and Metallurgy.
- [26] Nolan P. S., 1998, Flue Gas desulfurization in China, Babcock & Wilcox, International Electric Power for China.
- [27] Nolan P. S., 2000, Flue Gas Desulfurization, Technologies for Coal-Fired Power Plant, Low Rank Coal Utilization, ICS, Jakarta.
- [28] Nuning E. K. dan R. Azizah, 2005, Pengaruh Penggunaan Cerobong Asap Model "Water Spons Filter" (WSF) Terhadap Penurunan Kadar SO₂ Pada Industri Tahu di Sukun, Malang.
- [29] Peraturan Presiden No. 61 tahun 2011 tentang Rencana Aksi Nasional Penurunan Emisi Gas Rumah Kaca.
- [30] Tim Perumus Gubernur, 2010, Peraturan gubernur Sulawesi Selatan No. 69 tahun 2010 tentang baku mutu dan kriteria kerusakan lingkungan hidup, Setprov Sulawesi Selatan.
- [31] Agus Supriadi. PT INCO, Environmental Study of Sulfur and Sulfate Concentration in Soil and Water Sorowako and its Surrounding Area, Juni 2010.
- [32] PT INCO, Fuel consumption and cloud seeding activities, Januari 2011.
- [33] PT INCO. Environmental Study Of Sulfur And Sulfate Concentration In Soil And Water Sorowako And Its Surrounding Area, Sorowako, 2010.
- [34] Rader P., J. Augeli and S. Ahman (2000), Alstom Power FGD Technologies: SO₂ Compliance for Low Rank Coals at the Lowest Life Cycle Cost, Low Rank Coal Utilization, ICS, Jakarta.
- [35] Ravi K. Srivastava. (2000). U.S. Environmental Protection Agency National Risk Management Research Laboratory Research Triangle Part, NC.27711.
- [36] Reuther J. J. (1989), Applied Coal Combustion Basic, The Pennsylvania State University, USA.
- [37] Riyanto Marosin. 1995. Peralatan kontrol polusi udara. Teknologi Pengendalian dan Pengukuran Polusi Udara di Industri. UPT-LSDE, BPP Teknologi.
- [38] Saeni, M. S., 1989. Kimia Lingkungan.
- [39] Sato, T., Goro, T., Okabe, T., and Lawson, F., 2013, 'The Oxidation of Iron(II) Sulfate With Sulfur Dioxide and Oxygen Mixture,' *Bull. Chem. Soc. Jpn*, 57(8), 2082-2086.

- [40] Djayanti, S., Perancangan Prototipe Alat Pengendalian Pencemaran SO₂ dengan Teknologi Non Thermal Plasma. Balai Besar Teknologi Pencegahan Pencemaran Industri.
- [41] Sjahrul, M., 2001, Kimia Lingkungan. Fakultas MIPA. Universitas Hasanuddin. Makassar.
- [42] Smith, S. J., Andres, R., Conception, E., and Lurz, J.: Sulfur Dioxide Emissions: 1850–2000, JGCRI Report PNNL-14537, 2004.
- [43] Srivastava, A., and Kumar, R., 2001, Economics Valuation of Health Impact of Air Pollution in Mumbei, Environmental Monitoring and Assessment, 75: 135-143.
- [44] Sudrajad, Agung., 2006, Pencemaran Udara, Suatu Pendahuluan
- [45] Valix, M., and W. H. Cheung, 2002, Effect of sulfur on the mineral phases of laterite ores at high temperature reduction, Miner. Eng. 15: 523-530.
- [46] Youvial M, Sastrawinata, Yurismo (1999), Laporan Akhir Studi Kelayakan Pengendalian Emisi SO₂, UPT LSDE–BPPT, Maret 1999.
- [47] Yurismo H., Cahyadi, YenniWesti (2003), Pengendalian SO₂ dengan Sistem Injeksi Batu Kapur pada PLTU Batubara, Laporan Akhir RUT, UPT LSDE-BPPT.
- [48] Watson, J., Chow, J., Wang, X., Kohl, S., Sodeman, D., 2010. Measurement of Realworld Stack Emissions with a Dilution Sampling System (No. 010109-123109), Prepared by Desert Research Institute, Reno, NV, for Ft. McMurray, AB, Canada, Wood Buffalo Environmental Association.
- [49] Xiao, H. Y., Liu, C. Q., 2002. Sources of nitrogen and sulfur in wet deposition at Guiyang, southwest China. Atmospheric Environment 36, 5121-5130.
- [50] Zhang, W., P. Singh and D. M. Muir, 2000, SO₂/O₂ as an oxidant in hydrometallurgy, Miner. Eng. 13(13), 1319-1328.
- [51] Zhao, F., Knights, J., Hu, Z., McGrath, S., 2003. Stable sulfur isotope ratio indicates long-term changes in sulfur deposition in the Broadbalk experiment since 1845. Journal of Environmental Quality 32, 33-39.