Experimental Investigation of the Effect of Tilt Angle on the Dust Photovoltaic Module

Tariku Negash, Tasew Tadiwose

Department of Mechanical Engineering, Debre Markos University, Debre Markos, Ethiopia

Email address:

thismuch@ymail.com (T. Negash)

To cite this article:

Tariku Negash, Tasew Tadiwose. Experimental Investigation of the Effect of Tilt Angle on the Dust Photovoltaic Module. *International Journal of Energy and Power Engineering*. Vol. 4, No. 4, 2015, pp. 227-231. doi: 10.11648/j.ijepe.20150404.15

Abstract: This research paper investigate the effect of tilt angle on the accumulation of dust PV module on energy production and presents a module for predicting soiling losses for eight different tilt angle (0° , 5° , 11.6° , 15° , 21.5° , 25° , 30° and 35°) including the latitude of Bahir Dar city (11.6°) and 21.5° tilt angle of 10Kw hybrid solar power plant PV module which is currently installed in Bahir Dar university. The study has shown that during the experimental investigation period there was total loss of insolation due to soiling was 32.32% and 4.8KWh/m² total energy has been absorbed at 0° tilt angle. Modules at 11.6° and 21.5° tilt angles the total insolation loss were 21.92% and 16.78% respectively since it has been covered with dust. Approximately both modules have 5.3KWh/m² of energy has been absorbed. However, at 25° tilt angle had a least insolation loss and largest amount of energy absorbed when compared to the remaining seven different tilt angles; it has only 10.77% of insolation loss and 5.7KWh/m² of energy has been absorbed. The remaining tilt angles of 5° , 15° , 30° and 35° the total insolation loss were 25.45%, 19.08%, 14.20%, and 12.54% respectively, and also the total energy of 5.08KWh/m², 5.52KWh/m², 5.2KWh/m² and 4.59 KWh/m² were absorbed respectively. Thus, soiling effect has present at any tilt angle, but the magnitude is evident: the flatter the solar module is placed the more energy it will lose.

Keywords: Solar PV, Soiling, Tilt Angle, Insolation Loss

1. Introduction

A solar Photovoltaic is a method of generating electrical power by converting the solar radiation into direct current electricity using semiconductors that exhibit the photovoltaic effect [1]. Photovoltaic system installation has played a big role in renewable energy because PV systems are pollution free, economically reliable for long-term operation and secure energy source. The major obstruction of PV technology is its high capital costs compared to conventional energy sources and also it is the more widely used technology all over the world; there is 100GW of solar PV now installed in our world [2, 3].

It is estimated that a total of some 5.3MWp of PV is now in use in Ethiopia. In April 2012 Ethiopia has established the first Polycrystalline solar PV module assembly plant with the cooperation of SKY Energy International, Metals and Engineering Corporation (METEC) and an Ethiopian state enterprise. The plant would expected to achieve 20% of Ethiopian power capacity coming from solar energy within the next five years including 3 Million solar home systems

distribution plan and may also be exported to a neighboring country [4]. Performance of these solar-photovoltaic (PV) system not only depends on its basic electrical characteristics; maximum power, tolerance rated value of percentage, maximum power voltage, maximum power current, open-circuit voltage (Voc), short-circuit current (Isc), maximum system voltage, but also is negatively influenced by several obstacles such as ambient temperature, relative humidity, dust storms and suspension in air, shading, global solar radiation intensity, spectrum and angle of irradiance [5]. The radiation received by cells in the PV module is lower than radiation reaching the module surface. The main causes of these energy difference are dirt accumulation on the surface of the modules, reflection and absorption losses by the materials covering the cells and the tilt angle of the PV module. To better understand the effect of tilt angle on soiling, one has to know how it affects the current of the PV modules as it is directly proportional to the irradiance reaching the solar cells. The incident irradiance on PV cells

inside a PV module and the operating temperature of PV cells primarily dictate the power output of module. On a dual axis tracker, when module surface and the incident light rays are perpendicular to each other, the power output will be the highest. Therefore, this study aims to provide a better understanding of the extent at which tilt angle affects the dust, and hence the performance, of PV modules.

2. Methodology

2.1. Description of the Study and Set up of the PV Module

Bahir Dar city is located at latitude of $11^{\circ}36'N$ and longitude of $37^{\circ}23'E$ respectively, and an elevation of 1,840 meters above sea level. [6]. Fig 1 shows four modules that, two modules were dirt and tilt different two angles and the other two modules were clean by washing water and detergent and tilt similar to the two dust modules. And also due to the location of Bahir Dar those four modules face towards south by using compass, since more near to the equator and the system were installed at a minimum height of 1.5 meter from the ground.

Fig. 1. Clean and dust PV module at 21.50 and 250 tilt angle.

2.2. Calibration and Linearity check of the PV Module

The international Electronic Commissions (IEC) 60904-10 standard describes the procedures utilized for determination of the degree of linearity of any photovoltaic device parameter in relation to a test parameter. A device is linear when it meets the requirements of IECat section 7.3, which is stated as follows. When some device is claimed to be linear, the applicable range of irradiance, voltage, temperatures, or other necessary conditions should also be stated. The requirements for the acceptable limits of non-linearity (variation) are:

- For the curve of short-circuit current versus irradiance, the maximum deviation from linearity should not exceed 2 %.
- For the curve of open-circuit voltage versus the irradiance logarithm, the maximum deviation from linearity should not exceed 5 %.
- If the temperature coefficient of short circuit current

doesn't exceed $0.1 \text{ }^{\circ}K$, the device can be regarded as linear in relation to this parameter [7, 8].

During the outdoor experiment, the temperature and the output voltage of all the modules were recorded simultaneously every 15 minute using a multi-meter and a digital thermometer. As well as the irradiance and the short circuit current flow that analysed the linearity of the experiment.

2.3. Properties of Dust Based on the Laboratory Testing

Due to small diameter and less density of dust, can be blows in the environment with natural force. This dust diameter that flows on Bahir Dar city that estimates around 0.5-150 microns [9]. However it will vary from place to place. Thus, the average particle diameter is used for this experiment by sieving the dust with diameter of 0.075mm and it distributed 25 gram amount of dust to each tilt angle of PV module to make dirty.

2.4. Hydrometer Analysis: Composition of the Finer Dust Particles

According to ASTM D 422 clays are defined as particles diameter of between 0.075mm to 0.005mm and silt particles less than 0.005mm in diameter. Thus, from the 50 gram sample test of dust silt and clay amount were 63.62% and 36.38% respectively. Fig 2 shows that percentage of finer versus grain size diameter (mm).

Fig. 2. Hydrometer analysis of percentage of passing versus diameter of particle size.

2.5. Experimental Set up and Data Collecting of Wind Speed

The vantage pro 2 instrument as shown below on Fig 3 that has been used to measure the weather condition of the environment (solar radiation, rainfall, etc). But, for this experiment it is only used to measure the wind speed of the environment close to the PV module installed. The instrument has been installed 2.5m away from the PV and at an average height of 1.7m. The wind data has been stored in the data logger of the wireless vantage pro 2 (Fig 4) devices and export the record data by connecting USB cable to the

personal computer. The wind speed and direction data were record for eight days within 30 minutes time interval. During this time the tilt angles are changed in two days interval.

Fig. 3. Set up of vantage pro2 with clean and dusty PV module.

Fig. 4. Wireless data logger.

2.6. Data Collecting System and Period of Experiment

On this outdoor experiment, a systematic series of measurements were conducted for several time periods corresponding for eight different tilt angles on soiling and clean PV. The experimental data collection was carried out, for 32 days (September 12 to October 16/2013) excluding the holiday and uncomfortable weather condition. Through those days the experiment was conducted before and after rainfall condition. Particularly, the performance of the clean pair panel was compared with the corresponding of the soiled pair panels under different tilt angle for four days each. The experiment was mostly measured under clear sky, and different atmospheric conditions (e.g. ambient temperature, humidity, wind velocity etc.), for 1 hour there were 4 measurements recorded (approximately one measurement per 15 minute). During the recording procedure the values of the current and voltage of the PV-panels were recorded along with the values of the ambient temperature and solar radiation (W/m²). The loss of energy conversion efficiency can be calculated using the equation (1).

$$E_{loss}(\%) = \frac{E_{c,max} - E_{d,max}}{E_{c,max}} \quad (1)$$

Where: - $E_{c,max}$: Energy of clean PV, $E_{d,max}$: Energy of dust PV and, $E_{loss}(\%)$: Percentile insolation loss.

3. Experimental Results Analysis and Discussion

3.1. Effect of Tilt Angle Before Rainfall

As shown in Fig 5, as the tilt angles becomes increasingly from the horizontal surface, the insolation loss or soiling effect increases. Energy losses was varied from 31.24% to 38.40% with 0° title angle (horizontal) solar modules. For the latitude of 11.6° energy loss is not as high, but still varied up to 24.68%, depending on the daylight conditions, the amount of dust it has been accumulating soil before rainfall. The 25° tilt angle of the PV module highly decreased the insolation loss from 17.56% to 13.14% than others of tilt angles and it absorbed high amount of energy through 4 days measurement, 1518.80 Wh/m² and 1298.03 Wh/m² on the clean and soiled PV module respectively. Fig. 6 illustrated that unexpected increasing of insolation losses at 30° and 35° tilt angles were conducted since there was Agro-stone dust particles are blowing on the environment near to the experiment site. For angle of 0°, 5° and 11.6° energy harness is very low but they have large insolation losses.

Fig. 5. Average Daily Insolation loss for each tilt angle: Sept12-28/2013.

Fig. 6. Total Daily Energy for clean and unclean solar PV before rainfall.

3.2. Effect of Tilt Angle After Rainfall

During this study from Sept 29- Oct16/2013, there was rainfall from 0.2mm to 34.5mm based on Bahir Dar city weather station data, and it did effectively clean the solar modules from dirt accumulation. However, when there was only 1mm of rainfall or less and no wind, it made the soiling effect much worse. Rainfall makes a difference, because rain can act to clean the modules.

As shown on Fig. 7 and 8, the insolation losses decreased linearly up to the 25° of tilt angle. Within 12.9mm average rainfall the drop energy a conversion loss for both the latitude (11.6°) and 15° tilt angle were decreased from 19.24% to 16.83% and from 15.89% to 13.67% through 4 day incessantly measurement respectively. However, with in 8.0mm rain fall from Oct.6 to Oct.9 for 21.5° and 25° tilt angle the energy losses were decreased from 11.26% to 9.67% and 7.17% to 5.61% respectively. Beside this, the drop of energy loss are low at 30° and 35° of tilt angle even if the tilt angle is high. This illustrates that the soiling effect on PV modules needs more work for long period of time that helps to quantify its effect. However, the rainfall that clean the dust PV modules, still there are insolation loss particularly at small tilt angles.

Fig. 7. Average Daily Insolation losses for each tilt angle: Sept.29-Oct. 16/2013.

Fig. 8. Total Daily Energy absorbed for clean and unclean solar PV before rainfall.

3.3. Effect of Tilt Angle Both Before and After Rainfall

To compare the insolation losses before and after the

rainfall, the averages were calculated four days each for before and after the rainfall. Fig. 9 bars represent a percentage loss of insolation between clean and soiled solar PV module before and after rainfall. The percentage differences of the insolation loss of before and after rainfall were: 2.80% and 11.18% at 0° and 21.5° tilt angle: that is the least and the highest value out of the entire tilt angle respectively.

Fig. 9. Soiling Comparison before and after rainfall from Sept.12/2013-Oct16/2013.

3.4. Effects of Wind Load on a Dust PV Module

As illustrated the above fig. 10 the wind load has less effect at 0° and 5° tilt angle to clean the dust PV module due to this there were least energy absorbed difference are shown. As increased the tilt angle the wind load has a power to blow the dust from PV module. Likewise, the amount of the energy absorbed increase as increase number of days. However, the two days variation of energy absorbed were large at 30° and 35° tilt angle the amount of energy absorbed as much as expected. This is due to large tilt angle of the dust PV module.

Fig. 10. Effect of wind load on a dust PV module.

3.5. Selected Tilt Angles Comparison Before and After Rainfall

Three different angles have been selected to compare the insolation loss at different rainfall amount of each tilt angle,

for instance: horizontal surface (0°), latitude of Bahir Dar city (11.6°), and the 10KW hybrid solar power plant of tilt angle in Bahira Dar University (21.5°). On Fig. 11 the insolation loss can be calculated by interpolated the measured rainfall data between upper and lower value of the insolation loss. This helps to quantify the direct relationship of amount of rainfall to the insolation loss. The insolation loss for each tilt angle at the 0 mm of rainfall was calculated the average total insolation loss of before rainfall. Thus at zero millimeter of rainfall the insolation loss was 33.59%, 25.29% and 22.21% at 0° , 11.6° and 21.5° tilt angle. On the day six the insolation loss was increased linearly at 11.6° and 21.5° during the 2 mm of rainfall. However, the insolation loss was decreased highly at the maximum of the rainfall of 16 mm that was 29.62%, 17.21% and 9.73% at 0° , 11.6° and 21.5° tilt angle respectively.

Fig. 11. Daily Interpolated Insolation Loss at different estimated rainfall.

4. Conclusion

The outdoor experimental result reveals that, for horizontal surface (0°) tilt angle, there was a total loss of 32.32% due to dust and around 4.8 KWh/m^2 total energy absorbed. Likewise the study showed that, for 11.6° and 21.5° tilt angles the total insolation losses were 21.92% and 16.78% respectively because of dust, but they have almost similar energy gained around 5.3 KWh/m^2 . This implied that the 11.6° and 21.5° tilt angles had a lower insolation loss than the horizontal surface tilt angle but large amount of energy was absorbed. However,

at 25° tilt angle had a least insolation loss and largest amount of energy absorbed when compared to the remaining seven different tilt angles; it was only 10.77% of insolation loss and 5.7 KWh/m^2 of energy was absorbed. The remaining tilt angle wherefor 5° , 15° , 30° and 35° the total insolation loss were 25.45%, 19.08%, 14.20%, and 12.54% and also the total energy absorbed were 5.08 KWh/m^2 , 5.52 KWh/m^2 , 5.2 KWh/m^2 and 4.59 KWh/m^2 respectively. Thus, the dust effect has been present at any angle, but the magnitude is varied: more energy will lose, when the solar modules flatter angle. Nevertheless, the effect of tilt angle on the dust is depending on the environmental condition.

References

- [1] PVeducation.org/pvcdrom/introduction/solar-energy.
- [2] JasimAbdulateef. Simulation of Solar Off- Grid Photovoltaic System for Residential Unit. *International Journal of Sustainable and GreenEnergy*. Special Issue: Engineering Solution for High Performance of Solar Energy System. Vol. 4, No. 3-1, 2014, pp. 29-33.
- [3] Solar Power Information (2009, 8 April 2011). 'Solar Panels' www.solarpower2day.net/solar-panels/.
- [4] Ethiopian Resource Group (2011): National Energy Network: Energy for Growth and Transformation
- [5] Salih Mohammed, Osama Ibrahim, KaleidWaleed. Performance Enhancement of PV Array Based on Water Spraying Technique. *International Journal of Sustainable and green Energy*. Vol. 4, No. 3-1, 2015, pp. 8-13.
- [6] http://en.wikipedia.org/wiki/Bahir_Dar 2014.
- [7] IEC 60904-10, International Electrotechnical Commission, *Photovoltaic devices: Methods of Linearity measurement*. 2011
- [8] Shaharian A. and Sulaiman, effect of dust on the performance of P module, Malaysia, 2011
- [9] AssefaDerebeZegeye, 'Assessment of Upland Erosion Processes And Farmer's Perception Of Land Conservation In Debre-Mewi Watershed, Near Lake Tana, Ethiopia', Cornell university May 2009'