Simulation Research on EGR Reducing NO_x Emission of Diesel Engine

Zhu Jian, Ren Hongjuan, Luo Yiping

College of Automobile Engineering, Shanghai University of Engineering Science, Shanghai, P.R. China

Email address:

371754791@qq.com (Zhu Jian), 122587984@qq.com (Ren Hongjuan), Lyp777@sina.com (Luo Yiping)

To cite this article:

Zhu Jian, Ren Hongjuan, Luo Yiping. Simulation Research on EGR Reducing NO_x Emission of Diesel Engine. *International Journal of Energy and Power Engineering*. Vol. 4, No. 5, 2015, pp. 275-279. doi: 10.11648/j.ijepe.20150405.16

Abstract: The model of diesel engine and its EGR model were established in the AVL BOOST. The model's validity was verified by comparing with the data of engine bench test. The working conditions selected were 25%, 50%, 75% and 100% load under rated speed. Simulation results show that with the augment of the EGR rate, NO_x emissions decreased. When the opening degree of the EGR change from 0 to 100%, the NO_x of each working conditions decrease 46.23%, 42.2%, 33.97% and 32.3% respectively. At the same time, with the EGR valve opening increase, the reduction of NO_x is extremely significant.

Keywords: EGR, AVL BOOST, NO_x, Simulation

1. Introduction

The NO_x emissions of diesel engine has been polluted environment and harmed human health^[1-2]. EGR technology, as a kind of internal purification measure, has been widely used in diesel engine^[3-4]. Domestic and foreign scholars have carried out extensive research on EGR technology to reduce NO_x emissions of diesel engine. Zhang Quanchang et al studied the influence of the exhaust gas recirculation on the NO_x and the particle of the diesel engine, the results showed that with the increased of EGR rate, the percentage of NO was decreased firstly, and then it was increased^[5]. Daniel W. Dickey et al were according to the experimental acquired that the NO_x emission reduced more than 50% when the EGR rate was 15%^[6]. Yang Shuai et al used BOOST to establish a model of the one-dimensional working model of the turbocharged direct injection diesel engine with EGR system, the simulation results showed that the air fuel ratio, cylinder pressure, cylinder temperature and exhaust temperature of the diesel engine were decreased after using EGR^[7]. Mattarelli E et al established a computational model for the engine cycle simulation at full load by using the WAVE code, the simulation results showed that the EGR rate played an important role in reduction of NO_x emission^[8]. Zhao Lianhang et al used AVL BOOST software to build the model of the EGR system of one heavy diesel machine, and studied different fuel proportion and EGR rate double factors influenced the engine combustion and nitrogen oxide emissions. The results showed that when the EGR rate increased, the nitrogen oxide emissions decreased^[9]. Wang Yingying et al used GT-POWER software to build the model

of diesel engine and the corresponding EGR system, and analyzed the effect of EGR rate on the performance of the whole diesel engine. The research shows that under different working conditions, the EGR rate could effectively reduce the nitrogen oxides emissions^[10].

Although there were a lot of experiments and simulations on EGR to reduce the NO_x emissions, it was necessary to study the effect of different EGR ratio on engine performance under different loads. In this paper, the diesel engine and its EGR model were built by BOOST software. Through adjusted the valve R to control EGR rate and selected a number of operating load of engine, and studied the effect of different EGR valve on the engine performance, and provided more basis for analyzing EGR reducing NO_x emissions.

2 The Simulation of EGR System

2.1. The Model of EGR System

The research object of this article was heavy type diesel engine, this diesel engine's specific technical parameters were shown in Tab. 1.

The engine combustion process has always followed the law of the conservation of energy and mass, so it could be closely relate to the whole cylinder by the energy conservation equation, the mass conservation equation and the gas state equation. Engine cylinder heat changes included the work by piston, the heat generated by burning fuel, wall heat loss and enthalpy flow caused by leakage. By the first law of thermodynamics could get the following formula:

$$\frac{d(mu)}{d\varphi} = -p \frac{dV_s}{d\varphi} + \frac{dQ_B}{d\varphi} - \sum \frac{dQ_w}{d\varphi} - h_{BB} \frac{dm_{BB}}{d\varphi} \quad (1-1)$$

Where m was mass of mixed gas in cylinder, kg; u was internal energy in cylinder, $kJ / kg \cdot mol$; p was pressure of

mixed gas in cylinder, MPa; V_s was cylinder working volume, L; Q_B was fuel burning heat, kJ; Q_w was heat loss of system boundary, kJ; φ was crank angle, CA; h_{BB} was enthalpy value of leakage, $kJ / kg \cdot mol$.

Tab. 1. Main structural parameters and operation parameters of diesel engine.

Form	Four stroke, turbocharged inter-cooled, direct injection	Inlet valve opening(CA)	Before Top Dead Center20℃
Rated power(kW)	276	Inlet valve closed(CA)	After Bottom Dead Center34℃
Rated speed(rpm)	2100	exhaust valve opening(CA)	Before Bottom Dead Center49℃
Bore/trip(mm/mm)	126/155	exhaust valve closed(CA)	After Top Dead Center21℃
Compression ratio	17:1	displacement(L)	11.596L
Ignition sequence	1-5-3-6-2-4	Each cylinder valve number	4

The equation of gas exchange process could be determined by the law of thermodynamics, and the quality changed in the cylinder can be obtained by the total quality of the flow:

$$\frac{dm}{d\varphi} = \frac{dm_B}{d\varphi} + \frac{dm_s}{d\varphi} - \frac{dm_e}{d\varphi} \quad (1-2)$$

Where m_B was mass of fuel in the cylinder, kg; m_s was mass of gas injected cylinder, kg; m_e was mass of gas

expelled from cylinder, kg.

Gas state equation:

$$p V_s = mRT \quad (1-3)$$

Where R was gas constant.

The equation of the thermodynamic process of the cylinder of diesel engine could be transformed from above equation:

$$\frac{dT}{d\varphi} = \frac{1}{m \left(\frac{\partial u}{\partial T} + \frac{\partial u}{\partial p} \frac{p}{T} \right)} \left[\frac{dQ}{d\varphi} \left(1 - \frac{u + \frac{\partial u}{\partial p} p}{H_u} \right) - \frac{dQ_w}{d\varphi} - \frac{dm_{BB}}{d\varphi} (h_{BB} - u - p \frac{\partial u}{\partial p}) - m \frac{\partial u}{\partial \lambda} \frac{d\lambda}{d\varphi} - p \frac{dV}{d\varphi} \left(1 - \frac{\partial u}{\partial p} \frac{m}{V_s} \right) \right] \quad (1-4)$$

Fig. 1. The model of diesel engine.

Fig. 2. The model of EGR system.

In the AVL BOOST software system, the simulation model of diesel engine and its EGR system were established. They were shown in Fig.1 and Fig.2. Modules used in this model include the system boundary, pipes, coolers, turbocharger, volume cavity, cylinder, etc. A large number of measurement points in the pipeline were defined, and these points setting could not affect the characteristics of flow. The fluid temperature, pressure, flow rate and other key parameters in the simulation model obtained through these points.

In the model: SB1、SB2 stood for the system boundary—the inlet and exhaust environment; TC1 stood for exhaust gas turbo; CO1、CO2 stood for intercooler; PL1 stands for inlet manifold; PL2、PL3 stood for exhaust manifold; C1-C6 stood for cylinder; J1、J2、J3 stood for pipeline connection point; R1 stood for pipe valve (EGR valve); 1-24 stood for the system connection line; MP1-MP13 stood for measurement point.

2.2. The Parameter Setting for Model of EGR System

In simulation process, the parameters setting for the model directly affected the accuracy of the whole system. In order to ensure the accuracy of the model parameters, the inputting of boundary conditions were based on the test. The parameters included structural parameters and thermodynamic parameters.

Structural parameters included the geometric sizes of the gas flow pipeline, the geometry size of cylinder combustion chamber and the size of cooler etc. The friction coefficient of the pipe wall was determined by the nature of the pipeline material. At the same time we also need to defined the flow coefficient of the pipeline which determined by the recommend value of the software and pipeline structure.

For a cylinder, the simulation calculation could not consider the flow characteristics of gas mixture in cylinder, only the heat engineering were analysis and calculation, and based on the combustion characteristics and the computational requirements. In this paper, the combustion model used MCC model^[11]. MCC (Mixing Controlled Combustion) model as a quasi-dimensional combustion model has greater advantages compared with zero dimensional combustion model,

especially in the study of NO_x emissions. We need to input the nozzle number, diameter, flow coefficient and fuel injection law of the simulation engine, in order to calculate the fuel jet velocity and jet kinetic energy.

$$\frac{d_Q}{d_\varphi} = C_{\text{mod}} f_1(M_F, Q) f_2(K, V) \quad (1-4)$$

$$f_1(M_F, Q) = M_F \frac{Q}{LCV} \quad (1-5)$$

$$f_2(K, V) = \exp(C_{\text{rate}} \frac{\sqrt{K}}{\sqrt[3]{V}}) \quad (1-6)$$

where C_{mod} is the model parameters, kJ/kg/°CA; V is the instantaneous cylinder volume, m³; C_{mod} is the constant Hybrid rates; φ is the Crank Angle, °CA; K is the turbulent kinetic energy density, m²/s²; M_F is the jet fuel quality, kg; LCV is the low calorific value, kJ/kg; Q is the accumulation of heat release, kJ.

2.3. The Calibration and Verification of Model of EGR System

The calculation model of diesel engine was established after the parameters set and many times calibration, and simulation results under the requirements condition of diesel engine obtained by AVL BOOST calculation program. The simulation results need to compare with the test data, and the specific validation indexes were the effective power, torque, fuel consumption rate and burst pressure.

Fig. 3 showed the external characteristic curve of the diesel engine. It concluded that the simulation values of the effective power, torque, fuel consumption rate and the burst pressure of the diesel engine could better match with the actually measured values, and the error values were within 5% which met the requirements of simulation calculation.

Fig. 3. The curve of external characteristic.

Fig. 4. Engine performance changed with the opening of EGR valve.

3. The Influence of the EGR System on Exhaust Emissions of Diesel Engine

3.1. The Impact of the EGR Opening on Engine Performance

Through the test and relevant literature, it was known that when the EGR rate was small, it could not only ensure the engine power loss was smaller, but also greatly reduced nitrogen oxide emissions. When the EGR rate was large, the exhaust gas in the intake lead to limit lean combustion resulted in severe vibrations generated in engine. These vibrations were not conducive to the normal work of the engine^[12].

Based on the above reasons, and the EGR valve was positive correlation with the EGR rate. The EGR valve was controlled within 0~100%, which can not only ensure the performance of the engine, but also can achieve the purpose of reducing the nitrogen oxide.

The working conditions selected were 25%, 50%, 75% and 100% load under rated speed, and the opening of EGR valve in the model was regulated in order to study the characteristics

of engine performance under different EGR rate. Calculation results were shown in Fig. 4.

By the Fig. 4, the maximum explosion pressure and the combustion temperature of the cylinder decreased by the improvement of the opening of EGR valve, but the reduction range was small. The maximum burst pressure of the cylinder was reduced 12.61bar at 100% load, the decrease amplitude was 6.5%, the maximum combustion temperature in the cylinder decreased 183K at 100% load, the decrease amplitude was 7.6%; the other operating conditions were also reduced, but the reduction amplitude was little. The main reason was that with the using of EGR, some of the waste gas enters into the intake and mixed with fresh air. Because of the high gas temperature and a large of chemically inert gas—CO₂ and H₂O, thus the composition and properties of the mixture gas were changed^[13].

3.2. The Impact of the EGR Opening on NO_x Emissions

Through controlled the opening of EGR valve, the curve of NO_x emissions were shown in Fig. 5.

Fig. 5. Curve of NO_x emission.

By Fig. 5 showed, with the increased of EGR rate, NO_x emissions decreased, when the opening of the EGR changed from 0 to 100%, the NO_x respectively decreased 9.5 g / kW · h, 7.46 g / kW · h, 5.8 g / kW · h, 3.78 g / kW · h under four working conditions. The reduction rates were 46.23%, 42.2%, 33.97% and 32.3%. Mainly due to the using of EGR system, the burning process of fuel delayed, the maximum explosion pressure and the combustion temperature in the cylinder reduced. The NO_x decreased in the cylinder due to the reduction of temperature, pressure, and oxygen concentrated^[14]. Under the high load, with the increased of the opening of EGR valve, the reduction of NO_x was very significant.

4. Conclusion

(1) The model of EGR system in this paper was verified by comparing with the data of engine bench test, and the error values were within 5% which met the requirements of simulation calculation.

(2) The maximum explosion pressure and the combustion temperature of the cylinder decreased by the improvement of the opening of EGR valve. The maximum burst pressure of the cylinder was reduced 12.61bar at 100% load; the maximum combustion temperature in the cylinder decreased 183K at 100% load, the reduction amplitude was 7.6%. Because of the EGR made some of the waste gas enters into the intake.

(3) When the opening of the EGR valve was changed from 0 to 100%, the NO_x emissions decreased respectively 9.5 g / kW · h, 7.46 g / kW · h, 5.8 g / kW · h, 3.78 g / kW · h under 100%, 75%, 50%, 25% load, and the maximum explosion pressure and the combustion temperature in the cylinder reduced because of EGR made the burning process of

fuel delayed, the maximum explosion pressure and the combustion temperature in the cylinder reduced.

References

- [1] Rao Peng Hui, Wu Da Wei. The survey of distribution of exhaust pollution of motor vehicle [J]. Journal of resource saving and environmental protection, 2013 (5): 58-62.
- [2] Xu Guang Jun. The formation mechanism and purifying measures for main pollutants of diesel engine [J]. Journal of liaoning transportation science and technology. 2005 (12): 75-77.
- [3] R. S. G. Baert, D. E. Bechman, Efficient EGR technology for future HD diesel engine emission targets, SAE paper 1999-01-0837.
- [4] Toshihiko, Hidetoshi. Electrically operated EGR valve that reduces automotive emissions. Mitsubishi Electric Advance, 1999 (86): 20-24.
- [5] Zhang Quanchang, Rao Mingfa, Zheng Zunqing, et al. Experimental study on the influence of exhaust gas recirculation on NO_x and particulate emission of diesel engine[J]. Journal of internal combustion engine, 2012 30 (4): 310-315.
- [6] Daniel W. Dickey, Thomas W. Ryan III, NO_x Control in Heavy-Duty Diesel Engine-What is the limit?, SAE 980174, 1998.
- [7] Yang Shuai, Zhou Yi, ZouRenling, et al. The one dimensional simulation of EGR influence on the working process of diesel engine [J]. Journal of agricultural machinery, 2008(39):11-14.
- [8] Mattarelli E, Bianchi G M, Ivaldi D. Experimental and numerical investigation on the EGR system of a new automotive diesel engine[C]. SAE Paper 2000-01-0224, 2000.
- [9] Zhao Lianhang. Simulation research on the work process of 4L20 diesel engine and characteristics of NO_x emission [D]. Dalian Maritime University, 2012.
- [10] Wang Yingying, Zhou Bin. Modeling and Simulation of 8V240ZJ diesel engine [J]. Internal combustion engine and power plant, 2012, (3): 37-40.
- [11] AVL BOOST User Guide Version [M]. Graz, Austria: AVL Company, 2008.
- [12] ZhouQi. The research for EGR system of automotive engine [D]. Tongji University, 2002.
- [13] Shen Zhaojie. Analysis of the combustion process of diesel engine and the research on the layer of EGR [D]. Jilin Univresity, 2013.
- [14] Wang Xu, Yao Ming Fa, Zheng Zun Qing. The study on influence of multiple injection and EGR coupling controlled for the performance and emissions of the engine [J]. Journal of internal combustion engine, 2010 (01): 103-108.