



Effects of Sole and Combined Physical Filtration Materials on Physicochemical and Microbiological Properties of Waste Waters

Akinbuwa Olumakinde^{1,*}, Agele Samuel²

¹Department of Plant Science and Biotechnology, Adekunle Ajasin University, Akungba Akoko, Nigeria

²Department of Crop, Soil and Pest Management, Federal University of Technology, Akure, Nigeria

Email address:

makindeakinbuwa@gmail.com (A. Olumakinde)

*Corresponding author

To cite this article:

Akinbuwa Olumakinde, Agele Samuel. Effects of Sole and Combined Physical Filtration Materials on Physicochemical and Microbiological Properties of Waste Waters. *Advances in Applied Physiology*. Vol. 6, No. 2, 2021, pp. 33-37. doi: 10.11648/j.aap.20210602.12

Received: September 6, 2021; **Accepted:** November 5, 2021; **Published:** November 17, 2021

Abstract: Agricultural re-use of waste waters is a feasible alternative for increasing water resources for agriculture. Several methods have been adopted for improving waste water quality for safe re-use in agriculture. However, these methods are complex and difficult to use by local farmers. Hence, a study was conducted to examine the effects of a simple and cost-effective waste water treatment methods on physicochemical and microbial properties of waste waters. The research was conducted in the Department of Crop, Soil and Pest Management, the Federal University of Technology, Akure (FUTA). Waste waters consisted of: fish pond effluent and municipal stream. Materials used for physical filtration of waste waters include: granite, rice husk, charcoal, and pure river sand. Prior to and after treatments, the waste waters were subjected to chemical analysis (pH, electrical conductivity (EC), Nitrate, Cl, P, Ca, and Mg), physical analysis (Total solid, Total dissolved solid and Total suspended solid), and microbiological analysis (Total faecal coliforms, bacteria, yeast and fungi). Results obtained showed that sole and combined applications of physical filtration materials significantly reduced microbial loads in waste waters. Similarly, significant reductions in total solid (TS), total suspended solid (TSS) and total dissolved solid (TDS) were obtained for waters filtered with the filtration materials, both in the single and combined applications. The highest significant pH, EC and chloride were recorded in untreated fishpond effluent (T₁), while fishpond effluent filtered with rice husk (T₅) recorded the highest Significant Ca and Mg. Highest significant Nitrate was recorded in municipal wastewater filtered with rice husk (T₁₁), while highest significant P was obtained at T₅ and T₁₁. Results of this research showed improvement in the quality parameters of waste waters filtered with sole and combined filtration materials.

Keywords: Cucumber, Microbiological Analysis, Municipal Stream

1. Introduction

Continuous rise in global population and industrialization has resulted to increases in the volume of waste generation including waste water yearly [1]. The indiscriminate discharge of waste waters into rivers and lakes without adequate treatment has resulted into contamination of water bodies in many regions of the world [2]. Contamination of water bodies has become a global concern as a result of the growing population of the world which is in boundless need of fresh water [3].

Waste water recycling has become a generally acceptable

approach in water management, and this has in great extent reduced the force enforced on available water supply due to population growth [4]. According to Heidarpour *et al.*, the recycling of waste waters for irrigation purpose will considerably reduce the amount of water that is required to be removed from global water sources [5]. Waste waters serve as good source of water and nutrients for crops, therefore, reuse of waste waters serve to maintain soil and crop productivity and protection of the environment [6]. Waste water also contains significant amounts of organic and inorganic nutrients, especially nitrogen (N), phosphorus (P), potassium (K) and micronutrients [7], hence, its reuse can

save a lot of fertilizer expenditures when used in agriculture [8].

However, the direct application of untreated waste waters on crop land is associated with a many risks such as Crop yields reduction, crop quality deterioration, contamination of crops with pathogens and intestinal helminthes [9]. Therefore, in order to reduce the health hazards and damage to the natural environment, waste waters must be treated before reuse especially for agricultural irrigation [10]. Waste water reuse in agriculture must comply with re-use standards to minimize environmental and health risks [11].

There are several methods/technologies for treating waste waters for re-use in agriculture. These methods are complex and difficult to use by local farmers. Also, high capital required for the construction of these waste water treatment systems as well as skilled staff needed to operate the systems, which even become more technical each day, are other limiting factors [12]. Hence, the need to provide a simple and cost effective treatment facility for wastewater re-use for agriculture.

2. Materials and Methods

2.1. Experimental Site

The experiment was carried out in the screen house of the Department of Crop, Soil and Pest Management, The Federal University of Technology, Akure.

2.2. Sources of Waste Water

Waste waters used for the experiment consist: (i) Fish pond effluent (FPE) which was collected from a local fish pond, Oda Road, Akure, Ondo State; and (ii) Municipal waste water (MWW) which was collected from a stream situated along FUTA South Gate, Akure, Ondo State.

2.3. Treatment of Waste Waters

Waste water treatment consisted of primary and secondary treatments. In the primary waste water treatment (PWWT), waste waters were allowed to settle in two separate clean basins for 24 hours. Solid and heavy particles, settled at the bottom of the basins, were removed, and the waters were carefully decanted to another separate two basins. Sodium hypochlorite (NaOCl) was applied as disinfectant to the decanted waters before they were subjected to secondary treatments. In the secondary waste water treatment (SWWT), the decanted waters from the PWWT were subjected to physical filtration using filtration materials solely and in combination. The filtration materials were applied in layers in the filtration facility constructed.

Treatments evaluated includes:

T₀=Borehole water (Control)

T₁=Untreated fish pond effluent

T₂=Fish pond effluent filtered with granite

T₃=Fish pond effluent filtered with charcoal

T₄=Fish pond effluent filtered with pure river sand

T₅=Fish pond effluent filtered with rice husk

T₆=Fish pond effluent filtered with combined physical filters

T₇=Untreated municipal waste water

T₈=Municipal waste water filtered with granite

T₉=Municipal waste water filtered with charcoal

T₁₀=Municipal waste water filtered with pure river sand

T₁₁=Municipal waste water filtered with rice husk

T₁₂=Municipal waste water filtered with combined physical filters

Each treatment was replicated four (4) times.

2.4. Analysis of Treated and Untreated Waste Waters

Prior to and after treatments, the waste waters were subjected to chemical, physical, and microbiological analyses. The pH of each water samples was determined using Metro pH meter model E250, and the EC was measured using conductivity meter. Total solids, dissolved solids and suspended solids were determined using the AOAC method of analysis (1984). Chloride ion in water samples was measured titrimetrically using the Mohr's method. Calcium and magnesium ions in water samples were determined using the EDTA titration method. Nitrate concentration in water samples was determined by sodium hydroxide colorimetric method.

Data were subjected to One-way ANOVA and means were separated with Tukey HSD test at 5% level of probability using SPSS 24.0 version.

3. Results and Discussion

The microbial and physicochemical properties of the treated waste waters, when compared to the untreated waste water samples, showed improved water Quality. The results revealed that separate and combined applications of physical filtration materials (granite, charcoal, pure river sand, and rice husk) reduced microbial loads (total faecal coliforms, bacteria, fungi, and yeast) after treatment. Several filtration materials have been adopted for waste water treatment such as sand, peat, wood by-products, biochar, coconut shells, glass bead, and other commercially available filtration materials which considerably reduced microbial loads [13]. Many studies have reported efficient bacteria (4.85–6.8 log₁₀ CFU/100 mL) and protozoa (2 log₁₀ CFU/100 mL) removal through filtration process [14, 15]. Morató *et al.* and Alufasi *et al.* reported that the effectiveness of filtration mainly depends on the characteristics of the pathogen and filtration media, including the type, texture, and size [16, 17]. The total coliforms of the treated waste waters varied between 14.67 to 225.33 MPN/100mL. These results conformed to the acceptable faecal coliform levels of ≤ 1000 MPN/100 mL in waste water for use in agriculture [18]. Bacterial population varied between 53.33 to 160.00 CFU/ml, yeast varied between 25.00 to 256.67 SFU/ml, and fungi varied between 7.00 to 31.00 SFU/ml. Jenkins *et al.* reported an average removal of 1.8 log₁₀ units, that is, 98.5% of fecal coli bacteria from a river water augmented with waste water over 10 weeks in a filter filled with fine sand [19]. However,

significant reductions in microbial loads were obtained when the physical filtration materials were used when combined (T₆ and T₁₂). This is in accordance with the result obtained by Huq *et al.* who reported that various types of sari cloth (fine mesh, woven cotton fabric) and nylon mesh used in single or multiple layers removed from water samples the zooplankton

and phytoplankton harboring *V. cholera* [20]. The treatments reduced *V. cholerae* concentrations by 95 to 99%. Also Serpieri *et al.* concluded that UV filters reduced microbiological contamination in treated waste water significantly [21].

Table 1. Microbial loads of treated and untreated waste waters.

Microbial load				
Water sources	Total faecal coliforms (MPN/100ml)	Bacteria (CFU/ml)	Yeast (SFU/ml)	Fungi (SFU/ml)
T ₀	0.00 ^a	16.33 ^a	0.00 ^a	0.00 ^a
T ₁	1100.00 ^g	1240.00 ^e	990.00 ^e	53.00 ^e
T ₂	225.33 ^f	163.33 ^d	115.00 ^{abc}	15.33 ^{bc}
T ₃	56.00 ^{bc}	71.33 ^{bc}	168.67 ^{bc}	14.67 ^{abc}
T ₄	150.00 ^e	160.00 ^d	201.67 ^c	12.33 ^{abc}
T ₅	97.00 ^{cd}	66.67 ^{bc}	25.00 ^{ab}	15.67 ^{bc}
T ₆	46.67 ^{ab}	53.33 ^b	27.67 ^{ab}	12.33 ^{abc}
T ₇	1263.02 ^h	1260.00 ^e	586.67 ^d	101.67 ^f
T ₈	143.33 ^{de}	80.00 ^c	122.67 ^{abc}	17.00 ^{bcd}
T ₉	145.33 ^{de}	110.00 ^{bc}	256.67 ^c	31.00 ^d
T ₁₀	225.33 ^f	90.54 ^{bc}	120.00 ^{abc}	23.67 ^{bc}
T ₁₁	149.32 ^c	83.33 ^c	33.33 ^{ab}	20.00 ^{bcd}
T ₁₂	14.67 ^{ab}	56.67 ^b	32.00 ^{ab}	7.00 ^{ab}

Mean with the same letter (s) in superscript on the same column are not significantly different at p=0.05 (Tukey HSD). T₀=Borehole water (Control), T₁=untreated fish pond effluent, T₂=fishpond effluent filtered with granite, T₃=fishpond effluent filtered with charcoal, T₄=fishpond effluent filtered with river sand, T₅=fishpond effluent filtered with rice husk, T₆=fishpond effluent filtered with combined physical filters, T₇=untreated municipal wastewater, T₈=municipal wastewater filtered with granite, T₉=municipal wastewater filtered with charcoal, T₁₀=municipal wastewater filtered with river sand, T₁₁=municipal wastewater filtered with rice husk, T₁₂=municipal wastewater filtered with combined physical filters

Table 2. Physical properties of treated and untreated waste waters.

Waste water physical properties			
Water sources	Total solid (mg/l)	Total dissolved solid (mg/l)	Total suspended solid (mg/l)
T ₀	16.01 ^a	8.64 ^a	8.17 ^a
T ₁	110.81 ^d	37.25 ^f	85.67 ^d
T ₂	48.33 ^b	20.66 ^{bcd}	28.39 ^b
T ₃	53.09 ^{bc}	22.91 ^{cde}	32.04 ^{bc}
T ₄	49.01 ^b	19.47 ^{bc}	30.79 ^{bc}
T ₅	49.99 ^{bc}	20.01 ^{bc}	30.66 ^{bc}
T ₆	48.72 ^{bc}	18.79 ^b	28.98 ^b
T ₇	141.49 ^e	52.43 ^g	93.97 ^e
T ₈	56.11 ^{bc}	25.43 ^c	35.50 ^c
T ₉	58.92 ^c	26.51 ^c	36.24 ^c
T ₁₀	54.07 ^{bc}	23.34 ^{cde}	34.02 ^{bc}
T ₁₁	54.70 ^{bc}	24.32 ^{de}	35.58 ^c
T ₁₂	50.84 ^{bc}	20.48 ^{bcd}	30.17 ^{bc}
WHO	-	500.00	-

Mean with the same letter (s) in superscript on the same column are not significantly different at p=0.05 (Tukey HSD). T₀=Borehole water (Control), T₁=untreated fish pond effluent, T₂=fishpond effluent filtered with granite, T₃=fishpond effluent filtered with charcoal, T₄=fishpond effluent filtered with river sand, T₅=fishpond effluent filtered with rice husk, T₆=fishpond effluent filtered with combined physical filters, T₇=untreated municipal wastewater, T₈=municipal wastewater filtered with granite, T₉=municipal wastewater filtered with charcoal, T₁₀=municipal wastewater filtered with river sand, T₁₁=municipal wastewater filtered with rice husk, T₁₂=municipal wastewater filtered with combined physical filters.

The performance of the constructed filtration facility as well as selected physical filtration materials such as granite, charcoal, rice husk and pure river sand were assessed in this study in terms of removal efficiency of Total Solid (TS), Total Suspended Solids (TSS), Total Dissolved Solid (TDS), Electric Conductivity (EC) along with improvement of pH quality of raw waste waters. The pH of the treated waters varied between 6.9 and 7.7 which agrees with the World

Health Organization 1989 and Food and Agricultural Organization 1999 standards and guidelines for safe reuse of waste water in agriculture. According to Gao *et al.*, microbial compositions are affected by the pH of solutions or substrate [22]. High TS, TDS, and TSS values were obtained for untreated wastewaters (Table 2). High TS, TDS, and TSS in untreated wastewaters (T₁ and T₇) is due to the existence of colloidal and non-settleable solids including large sand

particles, clay and fine silt. In the present study, significant reductions in TS, TDS, and TSS were obtained with the application of physical filtration materials, both in the single and combined applications. The low levels of total solids (TS), total dissolved solids (TDS) and total suspended solids (TSS) in the treated waste waters were similar to earlier reports of Rasool et al. who reported about 87% reduction in TS, 62.8% reduction in TDS, and 99.9% reduction in TSS while using pilot-scale stone media trickling filter [23]. In addition, Khan et al. reported reduction in TDS (66%) and TSS (100%) by integrating stone media trickling filter with sand column filter [24]. The treated wastewater was found to be feasible for agriculture and safe disposal based on the recommended TDS (<1000 mg/L) and TSS (25–80 mg/L) values [25]. Reduced EC and chloride concentration were also recorded in treated waste waters. EC is used to indicate the salinity potential of water by measuring the current

carrying capacity due to the presence of free ionized constituents [26, 27]. The permissible limit of EC by FAO is 1400 $\mu\text{S}/\text{cm}$ [28]. The EC values of untreated waste waters (T_1 and T_7) were observed as 1321.33 $\mu\text{S}/\text{cm}$ and 943.67 $\mu\text{S}/\text{cm}$ respectively. In the present study, significant reductions in EC values were found with application of the physical filters, both in the sole and combined applications. Pitchard et al. opined that the reductions in the TSS play a key role in the decline of EC values [29]. Also, Khan et al. found out that fixed biofilm reactor integrated with a sand column filter was effective in reduction of the EC value [24]. The results of this research also showed that chloride concentrations in the treated waste waters is far below the concentration of chlorides (250 mg/liter) for discharge into the receiving environment [30]. Similarly, nitrate, Ca, Mg, and P values obtained for treated waste waters fell within the recommended WHO guidelines of 10 mg/L [25].

Table 3. Chemical properties of treated and untreated waste waters.

Chemical Compositions							
Water sources	pH	Ec ($\mu\text{S}/\text{cm}$)	Cl (mg/l)	Ca (ppm)	Mg (ppm)	N (mg/l)	P (ppm)
T_0	6.71 ^a	240.00 ^a	53.64 ^a	32.25 ^{def}	19.26 ^g	4.30 ^d	0.65 ^a
T_1	7.81 ^g	1321.33 ^h	46.28 ^a	28.15 ^{bcd}	16.83 ^f	5.05 ^f	1.49 ^{bc}
T_2	7.40 ^{de}	613.67 ^f	216.28 ^c	33.23 ^{ef}	19.83 ^h	4.54 ^{de}	1.67 ^c
T_3	7.30 ^{cd}	328.33 ^b	324.82 ^f	26.12 ^{bc}	16.99 ^f	4.42 ^d	2.04 ^c
T_4	7.30 ^{cd}	415.67 ^d	127.81 ^b	26.25 ^{bc}	15.62 ^e	4.51 ^{de}	1.67 ^c
T_5	6.90 ^{ab}	286.67 ^{ab}	223.65 ^c	28.31 ^{cd}	12.25 ^c	4.75 ^{de}	24.54 ^g
T_6	7.05 ^{bc}	392.00 ^{cd}	193.69 ^{cd}	32.29 ^{def}	19.23 ^g	4.57 ^{de}	4.80 ^d
T_7	7.44 ^{def}	949.33 ^g	53.23 ^a	6.52 ^a	3.64 ^a	2.50 ^a	1.82 ^c
T_8	7.70 ^{fg}	550.00 ^e	177.85 ^b	23.31 ^b	13.83 ^c	3.13 ^b	0.84 ^a
T_9	7.70 ^{fg}	648.67 ^b	186.32 ^c	40.17 ^g	24.26 ^j	3.62 ^c	0.46 ^a
T_{10}	7.65 ^{efg}	529.00 ^d	179.83 ^c	28.14 ^{bcd}	16.83 ^f	3.16 ^{de}	0.40 ^a
T_{11}	7.40 ^{de}	331.33 ^{bc}	213.92 ^{de}	31.54 ^{def}	10.85 ^b	3.66 ^c	18.83 ^f
T_{12}	7.20 ^{cd}	338.33 ^{bc}	107.27 ^b	34.05 ^f	20.44 ⁱ	3.41 ^{bc}	6.60 ^e
WHO	6.5-8.5	1400.00	250.00	75.00	50.00	10.00	200.00

Mean with the same letter (s) in superscript on the same column are not significantly different at $p=0.05$ (Tukey HSD). T_0 =Borehole water (Control), T_1 =untreated fish pond effluent, T_2 =fishpond effluent filtered with granite, T_3 =fishpond effluent filtered with charcoal, T_4 =fishpond effluent filtered with river sand, T_5 =fishpond effluent filtered with rice husk, T_6 =fishpond effluent filtered with combined physical filters, T_7 =untreated municipal wastewater, T_8 =municipal wastewater filtered with granite, T_9 =municipal wastewater filtered with charcoal, T_{10} =municipal wastewater filtered with river sand, T_{11} =municipal wastewater filtered with rice husk, T_{12} =municipal wastewater filtered with combined physical filters

4. Conclusion

Results of this research showed improvement in the quality parameters (physical, chemical and microbial) of waste waters filtered with sole and combined filtration materials (granite, charcoal, rice husk, and river sand). Total solid (TS), total dissolved solid (TDS) and total suspended solid (TSS) were highest in untreated municipal waste water (T_7) while pH and EC were highest in untreated fish pond effluent (T_1). Microbial loads were also higher in both untreated fish pond effluent (T_1) and untreated municipal waste water (T_7). However, Sole use of filtration materials (granite, charcoal, rice husk, and river sand) improved waste water quality (physical, chemical and municipal properties). Waste water quality was further enhanced upon treatment with combined filtration materials. There is need to assess the growth and yield responses of agricultural crops to the treated waste waters.

References

- [1] Thapliyal, A., Vasudevan, P., Dastidar, M. G., Tandon, M. and Mishra, S. (2011). Irrigation with domestic wastewater: responses on growth and yield of ladyfinger (*Abelmoschus esculentus*) and on Soil Nutrients. *Journal of Environmental Biology*. 32: 645-651.
- [2] Khan, S., Cao, Q., Zheng, Y. M., Huang, Y. Z. and Zhu, Y. G. (2008). Health risks of heavy metals in contaminated soils and food crops irrigated with wastewater in Beijing, China. *Environmental pollution*, 152 (3), 686-692.
- [3] Alfonso-Muniozguren, P., Lee, J., Bussemaker, M., Chadeesingh, R., Jones, C., Oakley, D. and Saroj, D. (2018). A combined activated sludge-filtration-ozonation process for abattoir wastewater treatment. *Journal of Water Process Engineering*, 25 (February), 157-163.

- [4] Zahedi, A., Monis, P., Gofon, A. W., Oskam, C. L., Ball, A., Bath, A., Bartkow, M., Robertson, I. and Ryan, U. (2018). Cryptosporidium species and subtypes in animals inhabiting drinking water catchments in three states across Australia. *Water Resources*, 134, 327–340.
- [5] Heidarpour, M., Mostafazadeh-Fard, B., Koupai, J. A. and Malekian, R. (2007). The effects of treated wastewater on soil chemical properties using subsurface and surface irrigation methods. *Agricultural Water Management*, 90: 87-94.
- [6] Alobaidy, A. H. M. J., Al-Sameraiy, M. A., Kadhem, A. J. and Majeed, A. A. (2010). Evaluation of treated municipal wastewater quality for irrigation. *Journal of Environmental Protection*, 1 (03), 216.
- [7] Ghafoor, A., Rauf, A. and Arif. M. (1996). Soil and plant health irrigated with Paharang drain sewage effluents at Faisalabad. Pakistan. *Journal of Agricultural Science*, 33: 73–76.
- [8] Ibrahim, M. and Salmon, S. (1992a). Chemical composition of Faisalabad city sewage effluents: Nitrogen, phosphorus and potassium contents. *Journal of Agricultural Resources*, 30: 381-390.
- [9] Zavadil, J. (2009). The effect of municipal wastewater irrigation on the yield and quality of vegetables and crops. *Soil and Water Resources*, 4 (3): 91-103.
- [10] Pereira, L. S., Cordery, I. and Iacovides, I. (2002). Coping with Water Scarcity. UNESCO, Paris.
- [11] Saldías, C., Speelman, S., Amerasinghe, P. and Van Huylbroeck, G. (2015). Institutional and policy analysis of wastewater (re) use for agriculture: case study Hyderabad, India. *Water Science and Technology*, 72 (2), 322-331.
- [12] Kivaisi, A. K. (2001). The potential for constructed wetlands for wastewater treatment and reuse in developing countries: a review. *Ecological engineering*, 16 (4), 545-560.
- [13] Nilsson, C., Renman, G., Westholm, L. J., Renman, A. and Drizo, A. (2013). Effect of organic load on phosphorus and bacteria removal from wastewater using alkaline filter materials. *Water research*, 47 (16), 6289-6297.
- [14] Sleytr, K., Tietz, A., Langergraber, G. and Haberl, R. (2007). Investigation of bacterial removal during the filtration process in constructed wetlands. *Science of the Total Environment*, 380 (1-3), 173-180.
- [15] Redder, A., Dürr, M., Daeschlein, G., Baeder-Bederski, O., Koch, C., Müller, R. and Borneff-Lipp, M. (2010). Constructed wetlands—Are they safe in reducing protozoan parasites. *International journal of hygiene and environmental health*, 213 (1), 72-77.
- [16] Morató, J., Codony, F., Sánchez, O., Pérez, L. M., García, J. and Mas, J. (2014). Key design factors affecting microbial community composition and pathogenic organism removal in horizontal subsurface flow constructed wetlands. *Science of the Total Environment*, 481, 81-89.
- [17] Alufasi, R., Gere, J., Chakaunya, E., Lebea, P., Parawira, W. and Chingwaru, W. (2017). Mechanisms of pathogen removal by macrophytes in constructed wetlands. *Environmental Technology Reviews*, 6 (1), 135-144.
- [18] Miranda, N. D., Oliveira, E. L. and Silva, G. H. R. (2014). Study of constructed wetlands effluent disinfected with ozone. *Water science and technology*, 70 (1), 108-113.
- [19] Jenkins, M. W., Tiwari, S. K., and Darby, J. (2011). Bacterial, viral and turbidity removal by intermittent slow sand filtration for household use in developing countries: Experimental investigation and modeling. *Water research*, 45 (18), 6227-6239.
- [20] Huq, A., Xu, B., Chowdhury, M. A., Islam, M. S., Montilla, R. and Colwell, R. R. (1996). A simple filtration method to remove plankton-associated *Vibrio cholerae* in raw water supplies in developing countries. *Applied and environmental microbiology*, 62 (7), 2508-2512.
- [21] Serpieri, N., Moneti, G., Pieraccini, G., Donati, R., Mariottini, E. and Dolara, P. (2000). Chemical and microbiological characterization of drinking water after filtration with a domestic-size charcoal column and ultraviolet sterilization. *Urban Water*, 2, 13-20
- [22] Gao, P., Xu, W., Sontag, P., Li, X., Xue, G., Liu, T. and Sun, W. (2016). Correlating microbial community compositions with environmental factors in activated sludge from four full-scale municipal wastewater treatment plants in Shanghai, China. *Applied Microbiology and Biotechnology*, 100 (10), 4663-4673.
- [23] Rasool, T., Rehman, A., Naz, I., Ullah, R. and Ahmed, S. (2018). Efficiency of a locally designed pilot-scale trickling biofilter (TBF) system in natural environment for the treatment of domestic wastewater. *Environmental technology*, 39 (10), 1295-1306.
- [24] Khan, Z. U., Naz, I., Rehman, A., Rafiq, M., Ali, N. and Ahmed, S. (2015). Performance efficiency of an integrated stone media fixed biofilm reactor and sand filter for sewage treatment. *Desalination and Water Treatment*, 54 (10), 2638-2647.
- [25] WHO. Guidelines for the Safe Use of Wastewater. Excreta and Greywater in Agriculture. Volume 2. Wastewater Use in Agriculture; WHO Press: Geneva, Switzerland, 2006.
- [26] Norton-Brandão, D., Scherrenberg, S. M. and van Lier, J. B. (2013). Reclamation of used urban waters for irrigation purposes—a review of treatment technologies. *Journal of environmental management*, 122, 85-98.
- [27] Khan, S. A., Sharma, G. K., Malla, F. A., Kumar, A. and Gupta, N. (2019). Microalgae based biofertilizers: a biorefinery approach to phycoremediate wastewater and harvest biodiesel and manure. *Journal of Cleaner production*, 211, 1412-1419.
- [28] FAO. Advances in the Assessment and Monitoring of Salinization and Status of Biosaline Agriculture. Reports of Expert Consultation Held in Dubai, United Arab Emirates; FAO: Rome, Italy, 2007.
- [29] Pritchard, M., Craven, T., Mkandawire, T., Edmondson, A. S. and O'Neill, J. G. (2010). A comparison between Moringa oleifera and chemical coagulants in the purification of drinking water—An alternative sustainable solution for developing countries. *Physics and Chemistry of the Earth, Parts A/B/C*, 35 (13-14), 798-805.
- [30] Ukpong, E. C. and Agunwamba, J. C. (2012). Dispersion Characteristics of Settleable and Dissolvable Pollutants in Waste Stabilization Ponds. *Global Journal of Engineering Research*, 11 (2), 87-98.