



# Estimation of Reference Evapotranspiration in Middle South Saurashtra Region of India Using Dominant Meteorological Variables

Manoj Gundalia<sup>1, \*</sup>, Mrugen Dholakia<sup>2</sup>

<sup>1</sup>Department of Civil Engineering, Dr. Subhash Technical Campus (GTU), Junagadh, India

<sup>2</sup>Department of Civil Engineering, L. D. College of Engineering, Ahmedabad, India

## Email address:

mjgundalia@gmail.com (M. Gundalia), mrug63@rediffmail.com (M. Dholakia)

## To cite this article:

Manoj Gundalia, Mrugen Dholakia. Estimation of Reference Evapotranspiration in Middle South Saurashtra Region of India Using Dominant Meteorological Variables. *American Journal of Water Science and Engineering*. Vol. 1, No. 2, 2015, pp. 15-22.

doi: 10.11648/j.ajwse.20150102.12

---

**Abstract:** In this paper attempt is made to estimate reference evapotranspiration ( $ET_o$ ) from standard meteorological observations. The FAO-56 Penman-Monteith method is the most physical, reliable and mostly used as a standard to verify other empirical methods. However, it needs a lot of different input parameters. Hence, in the present study, a model based on most dominant meteorological variables influencing  $ET_o$  is proposed to estimate  $ET_o$  in the Middle South Saurashtra region of Gujarat (India). The performance of five different alternative methods and proposed model is compared keeping the FAO-56 Penman-Monteith method as reference. The models are evaluated by using Nash-Sutcliffe efficiency coefficient (E), ( $R^2$ ), ( $d_r$ ), (RSR) and (MAE) statistical criterions. The results show that the developed model and Hargreaves and Samani (1985) method provide the most reliable results in estimation of ( $ET_o$ ), and it can be recommended for estimating ( $ET_o$ ) in the study region.

**Keywords:** Reference Evapotranspiration, Meteorological Variables, FAO-Penman-Monteith Method, Middle South Saurashtra Region

---

## 1. Introduction

The reference evapotranspiration ( $ET_o$ ) is a function of local weather, represents the evapotranspiration (ET) from a defined vegetated surface, and serves as an evaporative index by which users can predict ET for agricultural or landscaped areas. Reference evapotranspiration  $ET_o$  is an important agro meteorological parameter for climatological and hydrological studies, as well as for irrigation planning and management.  $ET_o$  can be applied to a wide variety of research problems in the field of agro meteorology and agricultural water management. Many applications require estimating  $ET_o$  in areas where meteorological measurements are limited. Numerous  $ET_o$  equations have been developed and used by researchers which have really left the question of the best method to be used unanswered [3] and [15]. Existing  $ET_o$  equations are in range from simple empirical temperature-based equations to complex multi-layer resistance based equations. The International Commission for Irrigation and Drainage and Food and Agriculture Organization of the United Nations have

recommended using the Penman–Monteith method as the standard method for estimating  $ET_o$ , and for appraising other methods [5] and [6].

The Penman–Monteith method is ranked as the best method for estimating daily and monthly  $ET_o$  in all the climates. This has been confirmed by many researches in the last decade [1], [7], [8], [9], [10], [12], [14], [20], [23], [24], [25], [27] and [28]. The FAO-56 PM is a physically based approach which requires measurements of air temperature, relative humidity, solar radiation, and wind speed. In most of the situations, stations with reliable data of these parameters are limited. Therefore FAO-56 PM method not appropriate in many such situations. Simple methods with fewer input parameters are better choice in such situation. This has created interest and has encouraged development of practical model, based on a reduced number of weather parameters for estimating  $ET_o$ .

In this study, dependency of controlling meteorological variables is compared and analyzed. Appropriate model

based on dependency of significant variables is then developed. The performances of radiation-based and temperature-based methods [13], [16], [21], [22] and [26] methods are compared and evaluated. Finally, the overall applicability of the selected methods and proposed model are examined by evaluation of  $ET_o$  predictability in the study region.

## 2. Study Area and Data Collection

Geographical Areas of Middle South Saurashtra region of Gujarat state (India) encompasses Junagadh district (lies between  $20^{\circ} 26'$  to  $21^{\circ} 24'$  North latitudes and  $69^{\circ} 24'$  to  $71^{\circ} 03'$  East longitudes) and Amreli district (lies between  $20^{\circ} 27'$  to  $22^{\circ} 15'$  North latitudes and  $70^{\circ} 18'$  to  $71^{\circ} 45'$  East longitudes) as shown in (Figure 1). The area is situated in semi-arid region with mean annual rainfall of 955 mm, mean maximum temperature  $33.70^{\circ}C$  and mean minimum temperature  $22.70^{\circ}C$ . Meteorological data of Junagadh and Amreli meteorological stations of Gujarat state (India) were used in this study. Junagadh station is located at latitude of  $21^{\circ} 31'$  N, longitude of  $70^{\circ}33'$  E, and 61m msl while the Amreli station is located at latitude of  $21^{\circ} 35'$  N, longitude of  $71^{\circ}12'$  E, and 130m msl. This region is characterized by a semi-arid climate, with warm and dry summers and mild winter conditions. The highest mean annual wind speed was observed 12.84 Km/h in the month of June whereas lowest mean annual wind speed was observed 3.10 Km/h in the month of November.

Daily meteorological data, including air temperature, wind speed, relative humidity, bright sunshine hours and evaporation for period of 21 years (1992-2012) were collected from Junagadh Agro meteorological Cell and Amreli Agricultural Research Station of Junagadh Agricultural University, Junagadh. The associate parameters like solar radiation, saturation vapor pressure and vapor pressure deficit were computed with standard meteorological formula as described in FAO. Out of this data set, 11 years data (1992-2002) were used for

calibration and 10 years data (2003-2012) were used for simulation.




Figure 1. Middle South Saurashtra Region of Gujarat State.

Periodic insufficient rainfall pattern, limited water storage capacity of aquifer and natural water conservation are vital issues for this region. Water availability is a critical factor in this area and therefore accurate estimation of  $ET_o$  is needed for water resources management, crop water use, farm irrigation scheduling, and environmental assessment.

## 3. Materials and Methods

All This study is done in four steps as following.

*First step*

Select appropriate methods by determining dependency of  $ET_o$ -PM on different meteorological variables. For better comparative evaluation, the dimensionless standardized values of each variable were computed and compared by using the transformation shown in equation 1.

$$Z_i = \frac{(X_i - \mu)}{\sigma} \tag{1}$$

Where X is a variate, i is the  $i^{th}$  value,  $\mu$  is the mean of X and  $\sigma$  is the standard deviation of X.




Figure 2. Dependency of  $ET_o$ -PM on  $T_{max}$  at Daily time-scale for Junagadh (1992-2002).




Figure 3. Dependency of  $ET_0-PM$  on  $R_s$  at Daily time-scale for Junagadh (1992-2002).




Figure 4. Dependency of  $ET_0-PM$  on  $R_s e^{T_{max}}$  at Daily time-scale for Junagadh (1992-2002).




Figure 5. Dependency of  $ET_0-PM$  on  $T_{max}$  at Daily time-scale for Amreli (1992-2002).




Figure 6. Dependency of  $ET_0-PM$  on  $R_s$  at Daily time-scale for Amreli (1992-2002).




Figure 7. Dependency of  $ET_o$ -PM on  $R_s e^{T_{max}}$  at Daily time-scale for Amreli (1992-2002).

Analyzed and compared the dependency of controlling meteorological variables like air temperature, vapor pressure and relative humidity on  $ET_o$  for the study area. Maximum air temperature ( $T_{max}$ ), radiation ( $R_s$ ) and the product ( $R_s e^{T_{max}}$ ) were found to be the most significant factors influencing  $ET_o$ -PM when tested by dependence analysis for calibration period (1992-2002) in the study area. The dependency of  $ET_o$ -PM on ( $T_{max}$ ), ( $R_s$ ) and ( $R_s e^{T_{max}}$ ) at daily time-scales was presented with  $R^2$  values in (Figure 2 to 7). Direct linear relationship of the product ( $R_s e^{T_{max}}$ ) with  $ET_o$ -PM has been found in dependency assessment for the study area and this relationship can be proposed and expressed as:

$$ET_o = a(R_s e^{T_{max}}) \quad (2)$$

Where, a is calibration constant

Estimate  $ET_o$  using above proposed equation 2.

Second step

The daily  $ET_o$  was calculated by FAO Penman Monteith method [4] based on equation 3.

$$ET_o = \frac{0.408 \Delta (R_n - G) + \gamma \frac{900}{T_m + 273} u_2 (e_s - e_a)}{\Delta + \gamma (1 + 0.34 u_2)} \quad (3)$$

where  $R_n$  is the net radiation at the crop surface ( $MJ m^{-2} d^{-1}$ ),  $G$  is the soil heat flux density ( $MJ m^{-2} d^{-1}$ ),  $T_m$  is the mean daily air temperature at 2 m height ( $^{\circ}C$ ),  $u_2$  is the wind speed at 2 m height ( $m s^{-1}$ ),  $e_s$  is the saturation vapor pressure ( $kP_a$ ),  $e_a$  is the actual vapor pressure ( $kP_a$ ),  $e_s - e_a$  is the saturation vapor pressure deficit (VPD) ( $kP_a$ ),  $\Delta$  is the slope vapor pressure curve ( $kP_a ^{\circ}C^{-1}$ ) and  $\gamma$  is the psychrometric constant ( $kP_a ^{\circ}C^{-1}$ ). The  $ET_o$  values estimated using the standard FAO-56 PM method ranged between a minimum  $3.30 mm d^{-1}$  in July to a maximum  $14.70 mm d^{-1}$  in June.

Third step

As we observed that ( $T_{max}$ ) and ( $R_s$ ) were significant factors influencing  $ET_o$ -PM in dependency assessment, hence, the temperature and radiation based methods for  $ET_o$  estimation can comparatively perform better. Compute  $ET_o$  based on meteorology parameters by five different temperature- radiation based methods:

Turc (1961)

$$ET_o = a \left. \begin{aligned} &\frac{T_m (R_s + 50)}{T_m + 15} \text{ if } RH > 50\% \\ &\frac{T_m (R_s + 50)}{T_m + 15} \left( 1 + \frac{50 - RH}{70} \right) \text{ if } RH < 50\% \end{aligned} \right\} \quad (4)$$

Where  $R_s$  is solar radiation ( $MJ m^{-2} d^{-1}$ ) and RH is relative humidity in %

Jensen and Haise (1963)

$$ET_o = C_T (T_m - T_x) R_s \quad (5)$$

Where  $C_T$  and  $T_x$  are constants expressed as

$$C_T = \frac{1}{\left[ \left( 45 - \frac{h}{137} \right) + \left( \frac{365}{e^0(T_{max}) - e^0(T_{min})} \right) \right]}$$

$$T_x = -2.5 - 0.14 (e^0(T_{max}) - e^0(T_{min})) \frac{h}{500}$$

Where h is the altitude of location in meter and  $e^0(T)$  saturation vapour pressure at the air temperature T ( $KP_a$ )

Hargreaves and Samani (1985)

$$ET_o = a((T_{max} - T_{min})^c (T_m + b) R_a \quad (6)$$

Where  $R_a$  is total extra-terrestrial solar radiation ( $MJ m^{-2} d^{-1}$ )

Priestley and Taylor (1972)

$$ET_o = a \frac{\Delta}{\Delta + \gamma} \frac{(R_n - G)}{\lambda} \quad (7)$$

Where  $\lambda$  is the latent heat of vaporization ( $MJ Kg^{-1}$ ) Makkink (1957)

$$ET_o = a \frac{\Delta}{\Delta + \gamma} \frac{(R_s - G)}{2.45} - b \quad (8)$$

Where a, b and c are calibration constants. The original parameters values of all the above selected methods are presented in (Table 1).

**Table 1.** Selected Methods with their Original Parameters Values (Parameters are Dimensionless).

Methods	Original Parameter Values		
	a	b	c
Turc (Equation (4))	0.0133	-	-
Jensen and Haise(Equation (5))	-	-	-
Hargreaves and Samani (Equation (6))	0.0023	17.80	0.50
Priestley and Taylor (Equation (7))	1.26	-	-
Makkink (Equation (8))	0.61	0.12	-

*Fourth step*

Compare the  $ET_o$  estimated by proposed developed expression (Equation 2) and five temperature-radiation based methods with standard FAO-PM method.

#### 4. Statistical Criteria

Geographical  $ET_o$ -PM method was selected as a benchmark method for comparison as it is a globally accepted model, used under a variety of climatic regimes and reference conditions. Daily  $ET_o$  values estimated from each empirical equation were compared with daily  $ET_o$  values calculated using  $ET_o$ -PM method. This paper places special emphasis on monsoon season comparison because it is the most significant period for hydrological studies. The performance of selected methods and proposed model against  $ET_o$ -PM values were evaluated using five quantitative standard statistical performance evaluation measures, Nash-Sutcliffe efficiency coefficient (E), coefficient of determination ( $R^2$ ), refined Willmott's index ( $d_r$ ) [29], root mean square of errors-observations standard deviation ratio (RSR) and mean absolute error (MAE).  $R^2$  describes the degree of collinearity while E reflects the overall fit between simulated and measured data. In general, model simulation can be judged as "satisfactory" if ( $R^2$  and E) > 0.50 and (RSR) < 0.70. The  $d_r$  is applied to quantify the degree to which values of  $ET_o$ -PM are captured by the selected methods. The range of  $d_r$  is from -1.0 to 1.0. A  $d_r$  of 1.0 indicates perfect agreement between model and observation, and a  $d_r$  of -1.0 indicates either lack of agreement between the model and observation or

insufficient variation in observations to adequately test the model. Mean absolute error (MAE) measure provides an estimate of model error in the units of the variable [18]. The MAE provides a more robust measure of average model error, since it is not influenced by extreme outliers. A higher MAE value indicates poor model performance and vice versa. MAE=0 indicates a perfect fit. MAE is the most natural and unambiguous measure of average error magnitude.

#### 5. Results and Discussion

Dependency analysis indicates that  $ET_o$ -PM was significantly influenced by ( $T_{max}$ ) and ( $R_s$ ) parameters, and the product ( $R_s e^{T_{max}}$ ) has direct relationship with  $ET_o$ -PM. In this study, model is proposed to estimate  $ET_o$  based on this relationship. Performance of the proposed model was compared with existing five different temperature-radiation based models. Calibration and validation were performed using data set from the year of 1992 to 2002 and from the year 2003 to 2012 respectively for both Junagadh and Amreli stations of the study area.

The selected methods may be reliable in the areas and over the periods for which they were developed, but large errors can be expected when they are generalized to other climatic areas without recalibrating their parameters. Accordingly, parameters of selected models were optimized to improve their performance for the study area. Optimized values of the parameters of models for both the stations are presented in (Table 2).

**Table 2.** Selected Methods and Proposed Model with their Optimized Parameters Values for Junagadh and Amreli Stations (Parameters are Dimensionless).

Methods	Junagadh			Amreli		
	a	b	c	a	b	c
Turc (Equation (4))	0.1636	-	-	0.1582	-	-
Jensen and Haise (Equation (5))	-	-	-	-	-	-
Hargreaves and Samani (Equation (6))	0.0006	0.0000	1.1172	0.0009	0.0000	0.8274
Priestley and Taylor (Equation (7))	2.0312	-	-	1.8459	-	-
Makkink (Equation (8))	3.0444	3.6908	-	2.5114	2.6655	-
Proposed Model (Equation (2))	0.0799	-	-	0.0666	-	-

**Table 3.** Performance of selected Methods and Proposed Model in Validation Period (2003-2012) for Junagadh.

Methods	E	$R^2$	$d_r$	RSR (mm)	MAE (mm)
Turc (1961)	0.21	0.67	0.54	0.89	2.08
Jensen and Haise (1963)	-2.30	0.90	0.01	1.81	4.47
Hargreaves and Samani (1985)	0.85	0.86	0.84	0.38	0.73
Priestley and Taylor (1972)	0.34	0.38	0.58	0.81	1.90
Makkink (1957)	0.38	0.38	0.62	0.78	1.74
Proposed Model	0.89	0.93	0.84	0.33	0.73


**Table 4.** Performance of selected Methods and Proposed Model in Validation Period (2003-2012) for Amreli.

Methods	E	R <sup>2</sup>	d <sub>r</sub>	RSR (mm)	MAE (mm)
Turc (1961)	0.28	0.75	0.55	0.85	1.42
Jensen and Haise (1963)	-2.71	0.86	-0.21	1.92	4.01
Hargreaves and Samani (1985)	0.84	0.91	0.81	0.40	0.59
Priestley and Taylor (1972)	0.54	0.63	0.63	0.67	1.17
Makkink (1957)	0.59	0.63	0.67	0.64	1.04
Proposed Model	0.91	0.94	0.85	0.30	0.46


The results of the statistical analysis of all the models versus FAO ET<sub>o</sub>-PM values in validation period (2003-2012) for Junagadh and Amreli stations are presented in (Table 3) and (Table 4) respectively. According to E, R<sup>2</sup>, and RSR criteria, except Turc and Jensen and Haise models, all other models give satisfactory results for Amreli station while for Junagadh station, Hargreaves and Samani and proposed model offer results within acceptable limits. d<sub>r</sub> and MAE criterias showed that Hargreaves and Samani and proposed model afforded reasonable results for Junagadh as well as for Amreli stations. The proposed model produced the highest E, R<sup>2</sup> and d<sub>r</sub> values 0.89, 0.93 and 0.84 respectively, and the lowest RSR and MAE values 0.33 mm and 0.73 mm respectively for Junagadh station. The Hargreaves and Samani method also produced E, R<sup>2</sup>, d<sub>r</sub>, RSR and MAE values within permissible limits 0.85, 0.86, 0.84, 0.38 and 0.73 respectively for Junagadh station. The proposed model attained the highest E, R<sup>2</sup> and d<sub>r</sub> values 0.91, 0.94 and 0.85

respectively, and the lowest RSR and MAE values 0.30 mm and 0.46 mm respectively followed by the Hargreaves and Samani method with E, R<sup>2</sup>, d<sub>r</sub>, RSR and MAE values 0.84, 0.91, 0.81, 0.40 mm and 0.59 mm respectively for Amreli station.

The Turc and Jensen methods had relatively poor performance for the study area. This might be due to there are no calibration parameters in the Jensen and Haise equation and the Turc equation has only one calibration parameter and it depends on meteorological variable RH, which was not significantly influenced on ET<sub>o</sub> in the study area. The proposed model with two calibration parameters and Hargreaves and Samani method with three recalibrated parameters produced the most reliable relationship with the standard FAO ET<sub>o</sub>-PM for daily time step. Performance of Hargreaves and Samani method and proposed model for daily time step in validation for Junagadh and Amreli are presented in (Figure 8) and (Figure 9) respectively.



**Figure 8.** Performance of Hargreaves method and proposed model at daily time step in validation period (2003-2012) for Junagadh.



**Figure 9.** Performance of Hargreaves method and proposed model at daily time steps in validation period (2003-2012) for Amreli.

## 6. Conclusions

In this study dependency analysis of  $ET_0$ -PM on different meteorological variables was made for the Middle South Saurashtra region of Gujarat state (India). A model based on significant meteorological variables influencing  $ET_0$  is proposed to estimate daily  $ET_0$  in the study area. Estimated  $ET_0$  values by using five selected methods (viz. Turc, Jensen and Hsieh, Hargreaves and Samani, Priestley and Taylor and Makkink methods) and proposed model are compared to the  $ET_0$  values calculated by the standard FAO  $ET_0$ -PM method for monsoon season. The results show that proposed model with single calibration parameter performed outstandingly best for all statistical tests and for both the stations. The performance of the Hargreaves and Samani method with recalibrated parameters has also been found to be reliable in the study area.

Therefore, a practical point of view, proposed model can be considered suitable to serve as a tool to estimate  $ET_0$  in the study area for monsoon season. Several authors have pointed out that a disadvantage of Penman's formula is the need for climate data which are not always available [2], [11], [17], and [19]. The Proposed model having fewer input parameters may be an attractive alternative to the more complicated FAO  $ET_0$ -PM method and could be recommended for  $ET_0$  computation under these prevailing conditions for the study area. This finding can help to overcome the shortage of data and will lead to minimize the time, cost, and equipment maintenance necessary for onsite monitoring. The methodology presented in this paper could be applied to the other regions for requisite regional calibrations.

## Acknowledgement

The authors are grateful to Junagadh Agro meteorological Cell and Amreli Agricultural Research Station of Junagadh Agricultural University, Junagadh (Gujarat), for providing all necessary meteorological data.

## References

- [1] Abdelhadi, A. W., Hata, T., Tanakamaru, T. A., & Tariq, M. A. (2000). Estimation of crop water requirements in arid region using Penman-Monteith equation with derived crop coefficients. A case study in Acala cotton in Sudan Gezira irrigated scheme. *Agric. Water Manage*: 45 (2), 203-214.
- [2] Abdulai, B. I., Stigter, C. J., Ibrahim, A. A., Adeeb, A. M., & Adam, H. S. (1990). Evaporation calculations for Lake Sennar. *Neth. J. Agric. Sci*: 38, 725-730.
- [3] Allen, R. G. (2000). *REF-ET for Windows: reference evapotranspiration calculator version 2.0*, University of Idaho Research and Extension Center, Kimberly, ID. Current online version: <http://www.kimberly.uidaho.edu/refet/>.
- [4] Allen, R. G., Pereira, L. S., Raes, D., & Smith, M. (1998). Crop Evapotranspiration: Guidelines for computing crop water requirements FAO, Irrigation and Drainage Paper No 56. *Food and Agriculture Organisation, Land and Water, Rome, Italy*: pp 300.
- [5] Allen, R. G., Smith, M. Pereira, L. S., & Perrier, A. (1994b). An update for the calculation of reference evapotranspiration. *ICID Bulletin*: 43 (2), 35-92.
- [6] Allen, R. G., Smith, M., Perrier, A., & Pereira, L. S. (1994a). An update for the definition of reference evapotranspiration. *ICID Bulletin*: 43 (2), 1-34.
- [7] Berengena, J., & Gavilan, P. (2005). Reference evapotranspiration estimation in a highly advective semiarid environment. *J. Irrig. Drain. Eng*: 121 (6), 427-435.
- [8] Beyazgul, M., Kayam, Y., & Engelsman, F. (2000). Estimation methods for crop water requirements in the Gediz Basin of Western Turkey. *J. Hydrol*: 229 (1-2), 19-26.
- [9] DelghaniSanij, H., Yamamoto, T., & Rasiah, V. (2004). Assessment of evapotranspiration models for use in semi-arid environments, *Agric. Water Manage*: 64 (2), 91-106.
- [10] Gavilan, P., Lorite, I. J., Tornero, S., & Berengena, J. (2006). Regional calibration of Hargreaves equation for estimating reference ET in a semiarid environment, *Agric. Water Manage*: 81 (3), 257-281.
- [11] Hargreaves, G. H. (1983). Discussion of 'Application of Penman wind function' by Cuenca, R. H. and Nicholson, M. J., *J. Irrig. and Drain. Engrg*: ASCE 109 (2), 277-278.
- [12] Hargreaves, G. H., & Allen, R. G. (2003). History and evaluation of Hargreaves evapotranspiration equation. *J. Irrig. Drain. Eng*: 129 (1), 53-63.
- [13] Hargreaves, G. H., & Samani, Z. A. (1985). Reference crop evapotranspiration from temperature. *Appl Engine Agric*: 1(2), 96-99.
- [14] Hussein, A. S. A. (1999). Grass ET estimates using Penman-type equations in Central Sudan. *J. Irrig. Drain. Eng*: 125 (6), 324-329.
- [15] Itenfisu, D., Elliott, R. Allen, R. G., & Walter, I. A. (2000). Comparison of reference evapotranspiration calculation across range of climates. In: Evans, R. G., Benham, B. L., & Trooien, T. P. (Eds). (2000). *Proceedings of the 4th Decennial Irrigation Symposium (ASAE), 14-16 November 2000, at Phoenix, AZ., U. S. A.*, 216-227.
- [16] Jensen, M. E., & Haise, H. R. (1963). Estimating evapotranspiration from solar radiation. *J. Irrig. Drainage: Div. ASCE*, 89, 15-41.
- [17] Keskin, M. E., & Terzi, O. (2006). Evaporation estimation models for Lake Egirdir, turkey. *Hydrol. Process*: 20, 2381-2391.
- [18] Legates, D. R., & McCabe, G. J. (1999). Evaluating the use of "goodness-of-fit" measures in hydrologic and hydroclimatic model validation. *Water Resources Res*: 35 (1), 233-241.
- [19] Linacre, E. T. (1993). Data-sparse estimation of lake evaporation, using a simplified penman equation. *Agricultural and Forest Meteorology*: 64, 237-256.

- [20] Lopez-Urrea, R., Martín de Santa Olalla, F., Fabeiro, C., & Moratalla, A. (2006). Testing evapotranspiration equations using lysimeter observations in a semiarid climate. *Agricultural Water Management*: 85, 15–26.
- [21] Makkink, G. F. (1957). Testing the Penman formula by means of lysimeters. *Journal of the Institution of Water Engineers*: 11, 277-28.
- [22] Priestley, C. H. B., & Taylor, R. J. (1972). On the assessment of the surface heat flux and evaporation using large-scale parameters. *Monthly Weather Review: Division of Atmospheric Physics, Commonwealth Scientific and Industrial Research Organization, Aspendale, Victoria, Australia*, 100, 81–92.
- [23] Todorovic, M. (1999). Single-layer evapotranspiration model with variable canopy resistance. *J. Irrig. Drain. Eng.*: 125 (5), 235-245.
- [24] Trajkovic, S. (2005). Temperature-based approaches for estimating reference evapotranspiration. *J. Irrig. Drain. Eng.*: 133 (4), 316-323.
- [25] Trajkovic, S., & Kolakovic, S. (2009). Evaluation of reference evapotranspiration equations under humid conditions. *Water Resour. Manage.*: 23, 3057-3067.
- [26] Turc, L. (1961). Estimation of irrigation water requirements, potential evapotranspiration: a simple climatic formula evolved up to date. *Ann. Agron.*: 12, 13-49.
- [27] Tyagi, N. K., Sharma, D. K., & Luthra, S. K. (2003). Determination of evapotranspiration for maize and berseem clover. *Irrig. Sci.*: 21 (4), 173-181.
- [28] Ventura, F., Spano, D., Duce, P., & Snyder, R. L. (1999). An evaluation of common evapotranspiration equation. *Irrig. Sci.*: 18 (4), 163-70.
- [29] Willmott, C. J., Robeson S. M., & Matsuura, K. (2012). A refined index of model performance. *Int. J. Climatol.*: 32, 2088–2094.